

SLA BB11R SW SO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







Similar to illustration

Minor component, major effect:

Clip-on attachment elements increase the mechanical resilience of the whole plug connection by

- securing the male connectors to the circuit board
- providing a vibration-proof connection between the sockets and the male connectors

Clip-on or pre-assembled - always the right solution:

- Hard-wearing, precise fitting dovetail joint
- Hard-wearing metal threaded inserts
- · Suitable for all outlet directions

Maximum stability, minimum effort:

- Extremely resilient for frequent fastening operations
- Complete set for easy selection

The result: soldering points, contacts and overall module are more resilient against mechanical stress such as vibrations and tensile loads.

General ordering data

Version	PCB plug-in connector, Accessories, Mounting block, black
Order No.	<u>1925080000</u>
Туре	SLA BB11R SW SO
GTIN (EAN)	4032248566181
Qty.	20 pc(s).
Product data	
Packaging	Box



SLA BB11R SW SO

Weidmüller Interface GmbH & Co. KG

EC002943

27-44-04-92

27-46-04-05

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Vet weight	0.9 g			
Environmental Product Comp	pliance			
REACH SVHC	Lead 7439-92-1			
Material data				
Colour	black	Colour chart (similar)	RAL 9011	
Storage temperature, min.	-40 °C	Storage temperature, max.	70 °C	
Operating temperature, min.	-50 °C	Operating temperature, max.	100 °C	
Temperature range, installation, min.	-25 °C Temperature range, installation, max. 100 °C			
remperature range, matanation, min.	20 0	romporatare range, motanation, max.		
Rated data acc. to IEC	20 0	remperature range, metallican, max.		
	IEC 60664-1, IEC 61984	rempetature range, motanidaen, max.		
Rated data acc. to IEC		remperature range, moralidation, max.		
Rated data acc. to IEC		VPE length	5 mm	

ETIM 6.0

ECLASS 9.0

ECLASS 10.0

IPC conformity	Conformity: The products are developed, manufactured and delivered according international recognized
	standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties
	in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.
Notes	 Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months

ETIM 7.0

ECLASS 9.1

ECLASS 11.0

Approvals

Α	n	n	rc		al	le	
	М	ν	·	, v	a		



EC002943

27-44-04-92

27-44-04-92

ROHS	Conform



SLA BB11R SW SO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings

Example of use

