


**WGKV 25 GY BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Similar to illustration

The WGK finger-proof-insulated enclosures are especially suitable as industrial electronic enclosures for frequency converters, power supplies or filter components which offer a convenient and reliable form of connection internally and externally. To match the wire guides to the installation requirements in the best possible way, Weidmüller offers two versions with horizontal (WGK) and vertical (WGKV) outlet directions.

**General ordering data**

|                     |                                                                                                                                                                           |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version             | OMNIMATE Power - series WGK, Feed-through terminal, Rated cross-section: 25 mm <sup>2</sup> , Screw connection, Wemid (PA), grey, Direct mounting, Feed-through (bushing) |
| Order No.           | <a href="#">1934070000</a>                                                                                                                                                |
| Type                | WGKV 25 GY BX                                                                                                                                                             |
| GTIN (EAN)          | 4032248588640                                                                                                                                                             |
| Qty.                | 25 pc(s).                                                                                                                                                                 |
| Product data        | IEC: 690 V / 101 A / 6 - 35 mm <sup>2</sup><br>UL: 600 V / 100 A / AWG 10 - AWG 3                                                                                         |
| Packaging           | Box                                                                                                                                                                       |
| Delivery status     | Discontinued                                                                                                                                                              |
| Creation date       | March 26, 2021 10:05:27 AM CET                                                                                                                                            |
| Available until     | 2016-04-27                                                                                                                                                                |
| Alternative product | <a href="#">2444820000</a>                                                                                                                                                |
| Catalogue status    | 12.03.2021 / We reserve the right to make technical changes.                                                                                                              |

## WGKV 25 GY BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                          |            |                 |            |
|--------------------------|------------|-----------------|------------|
| Height                   | 54 mm      | Height (inches) | 2.126 inch |
| Height of lowest version | 54 mm      | Length          | 75.75 mm   |
| Length (inches)          | 2.982 inch | Net weight      | 67.08 g    |
| Width                    | 15.1 mm    | Width (inches)  | 0.594 inch |

## System parameters

|                            |                             |                                            |                  |
|----------------------------|-----------------------------|--------------------------------------------|------------------|
| Product family             | OMNIMATE Power - series WGK | Wire connection method                     | Screw connection |
| Conductor outlet direction | 90°/270°                    | Fitted by customer                         | No               |
| Screwdriver blade          | 1.2 x 6.5                   | Tightening torque, min.                    | 4 Nm             |
| Tightening torque, max.    | 4.5 Nm                      | Clamping screw                             | M 6              |
| Stripping length           | 18 mm                       | Touch-safe protection acc. to DIN VDE 0470 | IP 20            |

## Material data

|                                       |            |                                       |        |
|---------------------------------------|------------|---------------------------------------|--------|
| Insulating material                   | Wemid (PA) | Colour                                | grey   |
| Colour chart (similar)                | RAL 7035   | UL 94 flammability rating             | V-0    |
| Contact material                      | E-Cu       | Contact surface                       | tinned |
| Storage temperature, min.             | -40 °C     | Storage temperature, max.             | 70 °C  |
| Operating temperature, min.           | -50 °C     | Operating temperature, max.           | 120 °C |
| Temperature range, installation, min. | -25 °C     | Temperature range, installation, max. | 120 °C |

## Conductors suitable for connection

|                                           |                    |
|-------------------------------------------|--------------------|
| Clamping range, min.                      | 4 mm <sup>2</sup>  |
| Clamping range, max.                      | 35 mm <sup>2</sup> |
| Wire connection cross section AWG, min.   | AWG 10             |
| Wire connection cross section AWG, max.   | AWG 3              |
| Solid, min. H05(07) V-U                   | 6 mm <sup>2</sup>  |
| Solid, max. H05(07) V-U                   | 16 mm <sup>2</sup> |
| Stranded, min. H07V-R                     | 10 mm <sup>2</sup> |
| Stranded, max. H07V-R                     | 35 mm <sup>2</sup> |
| Flexible, min. H05(07) V-K                | 6 mm <sup>2</sup>  |
| Flexible, max. H05(07) V-K                | 16 mm <sup>2</sup> |
| w. wire end ferrule, DIN 46228 pt 1, min. | 4 mm <sup>2</sup>  |
| w. wire end ferrule, DIN 46228 pt 1, max. | 25 mm <sup>2</sup> |

## WGKV 25 GY BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                     |                                        |                              |                          |       |
|---------------------|----------------------------------------|------------------------------|--------------------------|-------|
| Clampable conductor | Cross-section for conductor connection | Type                         | fine-wired               |       |
|                     |                                        | nominal                      | 4 mm <sup>2</sup>        |       |
|                     | wire end ferrule                       | Stripping length             | nominal                  | 18 mm |
|                     |                                        | Recommended wire-end ferrule | <a href="#">H4.0/18</a>  |       |
|                     | Cross-section for conductor connection | Type                         | fine-wired               |       |
|                     |                                        | nominal                      | 6 mm <sup>2</sup>        |       |
|                     | wire end ferrule                       | Stripping length             | nominal                  | 18 mm |
|                     |                                        | Recommended wire-end ferrule | <a href="#">H6.0/18</a>  |       |
|                     | Cross-section for conductor connection | Type                         | fine-wired               |       |
|                     |                                        | nominal                      | 10 mm <sup>2</sup>       |       |
|                     | wire end ferrule                       | Stripping length             | nominal                  | 18 mm |
|                     |                                        | Recommended wire-end ferrule | <a href="#">H10.0/18</a> |       |
|                     | Cross-section for conductor connection | Type                         | fine-wired               |       |
|                     |                                        | nominal                      | 16 mm <sup>2</sup>       |       |
|                     | wire end ferrule                       | Stripping length             | nominal                  | 18 mm |
|                     |                                        | Recommended wire-end ferrule | <a href="#">H16.0/18</a> |       |

Reference text Length of ferrules is to be chosen depending on the product and the rated voltage., The outside diameter of the plastic collar should not be larger than the pitch (P)

## Rated data acc. to IEC

|                                                                           |                        |                                                                |       |
|---------------------------------------------------------------------------|------------------------|----------------------------------------------------------------|-------|
| tested acc. to standard                                                   | IEC 60664-1, IEC 61984 | Rated current, min. number of poles (Tu=20°C)                  | 101 A |
| Rated current, max. number of poles (Tu=20°C)                             | 101 A                  | Rated voltage for surge voltage class / pollution degree III/3 | 690 V |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 6 kV                   |                                                                |       |

## Rated data acc. to CSA

|                                   |                                                                                     |                                   |                |
|-----------------------------------|-------------------------------------------------------------------------------------|-----------------------------------|----------------|
| Institute (CSA)                   |  | Certificate No. (CSA)             | 200039-1830694 |
| Rated voltage (Use group B / CSA) | 600 V                                                                               | Rated voltage (Use group C / CSA) | 600 V          |
| Rated current (Use group B / CSA) | 100 A                                                                               | Rated current (Use group C / CSA) | 100 A          |
| Wire cross-section, AWG, min.     | AWG 10                                                                              | Wire cross-section, AWG, max.     | AWG 3          |
| Reference to approval values      | Specifications are maximum values, details - see approval certificate.              |                                   |                |

## Rated data acc. to UL 1059

|                                       |                                                                                     |                                       |        |
|---------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|--------|
| Institute (cURus)                     |  | Certificate No. (cURus)               | E60693 |
| Rated voltage (Use group B / UL 1059) | 600 V                                                                               | Rated voltage (Use group C / UL 1059) | 600 V  |
| Rated current (Use group B / UL 1059) | 100 A                                                                               | Rated current (Use group C / UL 1059) | 100 A  |
| Wire cross-section, AWG, min.         | AWG 10                                                                              | Wire cross-section, AWG, max.         | AWG 3  |
| Reference to approval values          | Specifications are maximum values, details - see approval certificate.              |                                       |        |

## WGKV 25 GY BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Packing

|           |        |            |        |
|-----------|--------|------------|--------|
| Packaging | Box    | VPE length | 35 mm  |
| VPE width | 120 mm | VPE height | 330 mm |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001283    | ETIM 7.0    | EC001283    |
| ECLASS 9.0  | 27-14-11-34 | ECLASS 9.1  | 27-14-11-34 |
| ECLASS 10.0 | 27-14-11-34 | ECLASS 11.0 | 27-14-11-34 |

## Important note

## Notes

- Clearance and creepage distances to other components must be devised in accordance with the relevant application standard. This can be achieved in the device by full encapsulation or by the use of additional spacer plates.
- Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.
- Colours: SW = black; GN/YL = green/yellow; GY = grey
- Additional colours on request
- WGK: Rated voltage plastic walls: 1 - 6 mm = 800 V; metal walls: 1 - 4 mm = 800 V; metal walls: 4 - 6 mm = 690 V
- WGKV: Rated voltage plastic walls: 1 - 6 mm = 800 V; metal walls: 1 - 4 mm = 800 V; metal walls: 4 - 6 mm = 690 V
- WGK...VP: Rated voltage plastic walls: 1 - 6 mm = 800 V; metal walls: 1 - 2.5 mm = 800 V; metal walls: 2.5 - 4 mm = 690 V; metal walls: 4 - 6 mm = 500 V
- Wire-end ferrules are mandatory for stranded wires with more than 19 strands.
- Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months

## Approvals

## Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

## Downloads

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                    |


## WGKV 25 GY BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Dimensional drawing



### Derating curve

