

PB SUB-D ZF TERM PS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

General ordering data

Version	Sensor/Actuator plug-in connector
Order No.	1934200000
Type	PB SUB-D ZF TERM PS
GTIN (EAN)	4032248590575
Qty.	1 pc(s).
Delivery status	Discontinued
Available until	2018-10-01
Alternative product	1161880000

Creation date March 26, 2021 10:06:59 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

PB SUB-D ZF TERM PS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	49 g
------------	------

Temperatures

Humidity	Max. 75% at +25°C, non-condensing
----------	-----------------------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical specifications for sub-D connector

BUS PG interface	D-Sub 9-pole, Socket	BUS interface	D-Sub 9-pole, Pin
BUS, cable interface	Tension clamp connection	Data rate	12 MBit/s
Housing main material	PC UL 94 V-1	Humidity	Max. 75% at +25°C, non-condensing
Interlock	UNC4-40	Outgoing elbow	90°
Plug-in connector and pin assignment	In accordance with the PROFIBUS specification	Programming interface	Yes
Protection degree	IP40	Temperature range of housing	-25...+80 °C
Terminating resistor available	Yes		

Technical data customisable plug-in connectors

Cable diameter, max.	8 mm	Cable diameter, min.	4.5 mm
Housing main material	PC UL 94 V-1	Protection degree	IP40
Temperature range of housing	-25...+80 °C		

Classifications

ETIM 6.0	EC001132	ETIM 7.0	EC001132
ECLASS 9.0	27-44-03-02	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-02	ECLASS 11.0	27-44-03-02

Approvals

Approvals



ROHS

Conform