

# **SAIBW-8/9-M12**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

#### **General ordering data**

Version	Plugs prefabricated to customer spec., M12
Order No.	<u>1934890000</u>
Туре	SAIBW-8/9-M12
GTIN (EAN)	4032248592623
Qty.	1 pc(s).



# **SAIBW-8/9-M12**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

-			
Dim	ensions	and	weights

Net weight	29 g

#### **Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

## Technical data customisable plug-in connectors

Cable diameter, max.	8 mm	Cable diameter, min.	6 mm
Coding	Α	Contact surface	Gold-plated
Housing main material	Zinc diecast, nickel-plated	Number of poles	8
Plugging cycles	≥ 500	Pollution severity	3
Protection degree	IP67	Rated current	2 A
Rated voltage	60 V	Rated voltage (text)	250 V (4-pole) / 60 V (5- pole) / 30 V (8-pole)
Temperature range of housing	-40 +85 ° C	Type of connection	Screw connection

#### **Standards**

Connector standard IEC 61076-2-101

## Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC002635
ECLASS 9.0	27-44-01-02	ECLASS 9.1	27-44-01-03
ECLASS 10.0	27-44-01-02	ECLASS 11.0	27-44-01-02

#### **Approvals**

Approvals



ROHS Conform

#### **Downloads**

Engineering Data	<u>STEP</u>		
User Documentation	<u>Manual</u>		