

BV/SV 7.62HP/02 ARPL GR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







The pluggable connections for power electronics - optimised for modern drive technologies, e.g. motor starters, frequency converters and servocontrollers.

OMNIMATE Power sets the new standard - with increased safety and innovative solutions such as the pluggable shield, integrated signal contacts and onehanded operation.

The three product lines offer you further advantages:

- Application-oriented scalability: from the compact 4 mm² connector for 29 A (IEC) or 20 A (UL) up to the sturdy 16 mm² connector for 76 A (IEC) or 54 A (UL)
- Unlimited usage up to 1,000 V (IEC) or 600 V (UL)
- A variety of application optimised mounting options

Our Service:

Design your individual connectors simply by using the

General ordering data

Version	PCB plug-in connector, Accessories, Mounting plate, grey, Number of poles: 2
Order No.	<u>1937570000</u>
Туре	BV/SV 7.62HP/02 ARPL GR
GTIN (EAN)	4032248608850
Qty.	50 pc(s).
Product data	
Packaging	Вох



BV/SV 7.62HP/02 ARPL GR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany


www.weidmueller.com


Technical data


Dimensions and weights				
Net weight	2.24 g			
Material data				
Colour	grey	Colour chart (similar)	RAL 7035	
Storage temperature, min.	-40 °C	Storage temperature, max.	70 °C	
Operating temperature, min.	-50 °C	Operating temperature, max.	100 °C	
Temperature range, installation, min.	-25 °C	Temperature range, installation, max.	100 °C	
Rated data acc. to IEC				
tested acc. to standard	IEC 60664-1, IEC 61984			
Packing				
	_			
Packaging	Box	VPE length	25 mm	
VPE width	80 mm	VPE height	130 mm	
Classifications				
ETIM 6.0	EC002943	ETIM 7.0	EC002943	
ECLASS 9.0	27-44-04-92	ECLASS 9.1	27-44-04-92	
ECLASS 9.0 ECLASS 10.0	27-44-04-92	ECLASS 11.0	27-46-04-05	
Important note				
IDO 6 %				
IPC conformity	Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.			
Notes	Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months			
Approvals				
ROHS	Conform			
Downloads				
Approval/Certificate/Document of				
Conformity	Declaration of the Manufacturer			


SHOWN: ARPL BV/SV7.62HP/2AN


SHOWN: ARPL BV/SV7.62HP/4AN












ARPL BV/SV7.62HP/2AN



ARPL BV/SV7.62HP/4AN

PA 66/6 VO 30 GF GR	BV/SV7.62HP/4AN ARPL GR	1937580000
PA 66/6 VO 30 GF GR	BV/SV7.62HP/2AN ARPL GR	1937570000
WERKSTOFF MATERIAL	TYP PART NAME	BESTNR.
IMIAILNIAL	FARI NAME	CAI.NO.

