

**KLIPPON K61 VMQ**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**


The aluminium Klippon® K enclosures are suitable for use in an extremely wide range of different areas. Various components can be installed inside the enclosures, and will benefit in particular from the high temperature resistance, the excellent IP protection and the good impact resistance.

No matter what kind of application the customer is planning, Weidmüller is able to provide a wide range of aluminium enclosures precisely fitting the customer's requirements.

Klippon® K enclosures for hazardous areas are available on request.

Our extensive product range offers the following advantages:

- Available in two surface finishes: natural and powder-coated (RAL 7001)
- With chloroprene moulded seal as standard (silicone moulded seal optionally available)
- Standardised closure system with Torx slotted screw head for 19 enclosure sizes
- Mounting holes outside of the gasket area
- High IP protection classes: IP66, IP67 and IP68 according to DIN EN 60529
- Impact resistance of up to 7 (10) Joules
- The enclosures are approved according ATEX, IECEx, EAC, cULus, Russian Maritime Register and DNV GL as well as the empty enclosure standard.

- Suitable for railway applications according to EN 45545-2:2013
- Alloy is resistant to salt water
- Standardised distributor enclosures with threaded holes and a variety of terminal configurations

**General ordering data**

|            |                                                                                                                                                                         |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Klippon K (aluminium empty enclosure), Empty enclosure, Aluminium enclosure, Height: 160 mm, Width: 260 mm, Depth: 91 mm, Material: Aluminium AlSi12, untreated, silver |
| Order No.  | <a href="#">1939700000</a>                                                                                                                                              |
| Type       | KLIPPON K61 VMQ                                                                                                                                                         |
| GTIN (EAN) | 4032248616039                                                                                                                                                           |
| Qty.       | 1 pc(s).                                                                                                                                                                |

**KLIPPON K61 VMQ****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                             |             |                            |            |
|-----------------------------|-------------|----------------------------|------------|
| Depth                       | 91 mm       | Depth (inches)             | 3.583 inch |
| Height                      | 160 mm      | Height (inches)            | 6.299 inch |
| Mounting dimension - height | 110 mm      | Mounting dimension - width | 240 mm     |
| Net weight                  | 2,136 g     | Width                      | 260 mm     |
| Width (inches)              | 10.236 inch |                            |            |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Cable glands, left**

|     |   |     |   |
|-----|---|-----|---|
| M12 | 8 | M16 | 6 |
| M20 | 3 | M25 | 2 |
| M32 | 1 | M40 | 1 |

**Cable glands, right**

|     |   |     |   |
|-----|---|-----|---|
| M12 | 8 | M16 | 6 |
| M20 | 3 | M25 | 2 |
| M32 | 1 | M40 | 1 |

**Cable glands, top/bottom**

|     |    |     |    |
|-----|----|-----|----|
| M12 | 27 | M16 | 23 |
| M20 | 13 | M25 | 8  |
| M32 | 4  | M40 | 3  |

**Certificate numbers enclosure**

|                                         |                                           |                                        |                      |
|-----------------------------------------|-------------------------------------------|----------------------------------------|----------------------|
| Approval conditions                     | cULus, RMRS, DNV                          | Certificate No. (DNVGL)                | TAE00002SM           |
| Certificate No. (EAC)                   | RUC-DE.BE02.B.00173                       | Certificate No. (GERMLLOYD)            | TAE00002SM           |
| Certificate No. (MARITREG)              | 19.00108.272                              | Certificate no. (cULus)                | E197061              |
| Certificate no. Terminal Box (EAC)      | C-DE.AД54.B.00251/19<br>Ind. Terminal Box | Certificate no., empty enclosure (EAC) | C-DE.HB07.B.00089/20 |
| Declaration of Conformity No. (DoC LVD) | DE_PS2410_160412_001ISS01                 |                                        |                      |

## KLIPPON K61 VMQ

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## General information

|                                 |                                                                                                                    |                             |                       |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------|-----------------------|
| Access opening: height          | 151 mm                                                                                                             | Access opening: width       | 251 mm                |
| Areas of use                    | Process industry, Transportation, Marine engineering, Packaging industry, Harbour facilities, Machine construction | Enclosure attachment        |                       |
| Flange plate                    | No                                                                                                                 | Impact resistance           | Holes 6 mm<br>10.00 J |
| Integral fixing                 | Threaded holes M5                                                                                                  | Lid                         | Yes                   |
| Lid attachment                  | M6 torx stainless steel screws with slot                                                                           | Material                    | Aluminium AlSi12      |
| Material thickness              | 4.5 mm                                                                                                             | Material thickness of cover | 4 mm                  |
| Material thickness of enclosure | 4.5 mm                                                                                                             | Note: protection class      | IP68 (t=72h, h=1m)    |
| Operating temperature, max.     | 135 °C                                                                                                             | Operating temperature, min. | -50 °C                |
| Protection degree               | IP66, IP67, IP68                                                                                                   | Seal material               | Silicone              |
| Standards                       | EN 45545-2:2013                                                                                                    | Surface finish              | untreated             |
| Torque for lid screws           | 2.5 Nm                                                                                                             |                             |                       |

## horizontal assembly

|                             |      |                 |      |
|-----------------------------|------|-----------------|------|
| WDU 10 / ZDU 10             | 1x20 | WDU 16 / ZDU 16 | 1x16 |
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | 1x39 | WDU 4 / ZDU 4   | 1x33 |
| WDU 6 / ZDU 6               | 1x24 |                 |      |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000261    | ETIM 7.0    | EC000261    |
| ECLASS 9.0  | 27-18-01-01 | ECLASS 9.1  | 27-18-92-90 |
| ECLASS 10.0 | 27-18-01-01 | ECLASS 11.0 | 27-18-01-01 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E197061 |

## Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">C-DE.AJ54.B.00251.19 Ind. Terminal Box</a><br><a href="#">RUC-DE.BE02.B.00173</a><br><a href="#">TAE00002SM</a><br><a href="#">19.00108.272</a><br><a href="#">EU Declaration of Conformity - Klippion K Empty Enclosures - DoC DE PS2410 160412 001ISS01</a><br><a href="#">DoM Klippion K salt water resistance</a><br><a href="#">DoM Klippion K EN 45545-2 2013 Railway</a> |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                                                                                                                                                                                                                        |
| Engineering Data                            | <a href="#">EPLAN</a>                                                                                                                                                                                                                                                                                                                                                                       |
| Tender specification                        | <a href="#">Klippion K61 VMQ_1939700000_DE</a><br><a href="#">Klippion K61 VMQ_1939700000_EN</a>                                                                                                                                                                                                                                                                                            |
| User Documentation                          | <a href="#">Assembly guidelines - empty enclosures</a>                                                                                                                                                                                                                                                                                                                                      |

## KLIPPON K61 VMQ

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Dimensioned drawing

