


**SVZ 7.62HP/04/180SFC SN BK BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

High-performance male header with the proven, 100% maintenance-free Weidmüller steel clamping yoke. Side-by-side mounting without sacrificing any poles or with patented multifunction flange for secure, fast fixing without tools. Maximum connection and operating reliability thanks to a mating profile that prevents incorrect connection, unique coding diversity, incorrect wiring protection. Suitable for labelling.

**General ordering data**

|              |                                                                                                                                 |
|--------------|---------------------------------------------------------------------------------------------------------------------------------|
| Version      | PCB plug-in connector, male plug, 7.62 mm, Number of poles: 4, 180°, Clamping yoke connection, Clamping range, max.: 6 mm², Box |
| Order No.    | <a href="#">1951010000</a>                                                                                                      |
| Type         | SVZ 7.62HP/04/180SFC SN BK BX                                                                                                   |
| GTIN (EAN)   | 4032248629916                                                                                                                   |
| Qty.         | 100 pc(s).                                                                                                                      |
| Product data | IEC: 1000 V / 57 A / 0.2 - 10 mm²<br>UL: 600 V / 42 A / AWG 24 - AWG 8                                                          |
| Packaging    | Box                                                                                                                             |

Creation date March 26, 2021 2:19:53 PM CET

## SVZ 7.62HP/04/180SFC SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 24.36 g |
|------------|---------|

## System Parameters

|                                              |                                      |                                            |                   |
|----------------------------------------------|--------------------------------------|--------------------------------------------|-------------------|
| Product family                               | OMNIMATE Power - series BV/SV 7.62HP | Type of connection                         | Field connection  |
| Wire connection method                       | Clamping yoke connection             | Pitch in mm (P)                            | 7.62 mm           |
| Pitch in inches (P)                          | 0.3 inch                             | Conductor outlet direction                 | 180°              |
| Number of poles                              | 4                                    | L1 in mm                                   | 22.86 mm          |
| L1 in inches                                 | 0.9 inch                             | Number of rows                             | 1                 |
| Pin series quantity                          | 1                                    | Rated cross-section                        | 6 mm <sup>2</sup> |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch               | Touch-safe protection acc. to DIN VDE 0470 | IP20 plugged      |
| Volume resistance                            | 4.50 mΩ                              | Can be coded                               | Yes               |
| Stripping length                             | 12 mm                                | Tightening torque for screw flange, min.   | 0.2 Nm            |
| Tightening torque for screw flange, max.     | 0.3 Nm                               | Tightening torque, min.                    | 0.5 Nm            |
| Tightening torque, max.                      | 0.6 Nm                               | Clamping screw                             | M 3               |
| Screwdriver blade                            | 0.6 x 3.5                            | Plugging cycles                            | 25                |

## Material data

|                                       |                    |                                       |                     |
|---------------------------------------|--------------------|---------------------------------------|---------------------|
| Insulating material                   | PA GF              | Colour                                | black               |
| Colour chart (similar)                | RAL 9011           | Insulating material group             | II                  |
| Comparative Tracking Index (CTI)      | ≥ 500              | Insulation strength                   | ≥ 10 <sup>8</sup> Ω |
| UL 94 flammability rating             | V-0                | Contact base material                 | Copper alloy        |
| Contact material                      | Copper alloy       | Contact surface                       | tinned              |
| Layer structure of plug contact       | 4...6 µm Sn glossy | Storage temperature, min.             | -40 °C              |
| Storage temperature, max.             | 70 °C              | Operating temperature, min.           | -50 °C              |
| Operating temperature, max.           | 125 °C             | Temperature range, installation, min. | -25 °C              |
| Temperature range, installation, max. | 125 °C             |                                       |                     |

## Conductors suitable for connection

|                                                                      |                         |
|----------------------------------------------------------------------|-------------------------|
| Clamping range, min.                                                 | 0.2 mm <sup>2</sup>     |
| Clamping range, max.                                                 | 6 mm <sup>2</sup>       |
| Wire connection cross section AWG, min.                              | AWG 22                  |
| Wire connection cross section AWG, max.                              | AWG 8                   |
| Solid, min. H05(07) V-U                                              | 0.2 mm <sup>2</sup>     |
| Solid, max. H05(07) V-U                                              | 6 mm <sup>2</sup>       |
| Flexible, min. H05(07) V-K                                           | 0.5 mm <sup>2</sup>     |
| Flexible, max. H05(07) V-K                                           | 10 mm <sup>2</sup>      |
| w. plastic collar ferrule, DIN 46228 pt 4, 0.25 mm <sup>2</sup> min. |                         |
| w. plastic collar ferrule, DIN 46228 pt 4, 6 mm <sup>2</sup> max.    |                         |
| w. wire end ferrule, DIN 46228 pt 1, 0.25 mm <sup>2</sup> min.       |                         |
| w. wire end ferrule, DIN 46228 pt 1, 6 mm <sup>2</sup> max.          |                         |
| Plug gauge in accordance with EN 60999 a x b; ø                      | 2.8 mm x 2.0 mm; 2.4 mm |

## SVZ 7.62HP/04/180SFC SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                                        |                                                                                                                                                                        |                              |                             |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------|
| Clampable conductor                    | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 0.5 mm <sup>2</sup>         |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 14 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H0.5/18 OR</a>  |
| Cross-section for conductor connection |                                                                                                                                                                        | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 1 mm <sup>2</sup>           |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 15 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H1.0/18 GE</a>  |
| Cross-section for conductor connection |                                                                                                                                                                        | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 1.5 mm <sup>2</sup>         |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 15 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H1.5/18D SW</a> |
|                                        |                                                                                                                                                                        | Stripping length             | nominal 12 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H1.5/12</a>     |
| Cross-section for conductor connection |                                                                                                                                                                        | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 0.75 mm <sup>2</sup>        |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 14 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H0.75/18 W</a>  |
| Cross-section for conductor connection |                                                                                                                                                                        | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 2.5 mm <sup>2</sup>         |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 14 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H2.5/19D BL</a> |
|                                        |                                                                                                                                                                        | Stripping length             | nominal 12 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H2.5/12</a>     |
| Cross-section for conductor connection |                                                                                                                                                                        | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 4 mm <sup>2</sup>           |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 12 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H4.0/12</a>     |
|                                        |                                                                                                                                                                        | Stripping length             | nominal 14 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H4.0/20D GR</a> |
| Cross-section for conductor connection |                                                                                                                                                                        | Type                         | fine-wired                  |
|                                        |                                                                                                                                                                        | nominal                      | 6 mm <sup>2</sup>           |
| wire end ferrule                       |                                                                                                                                                                        | Stripping length             | nominal 14 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H6.0/20 SW</a>  |
|                                        |                                                                                                                                                                        | Stripping length             | nominal 12 mm               |
|                                        |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H6.0/12</a>     |
| Reference text                         | The outside diameter of the plastic collar should not be larger than the pitch (P). Length of ferrules is to be chosen depending on the product and the rated voltage. |                              |                             |

## SVZ 7.62HP/04/180SFC SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Rated data acc. to IEC

tested acc. to standard

IEC 60664-1, IEC 61984

Rated current, max. number of poles  
(Tu=20°C)

41 A

Rated current, max. number of poles  
(Tu=40°C)

41 A

Rated voltage for surge voltage class /  
pollution degree III/2

1,000 V

Rated impulse voltage for surge voltage  
class/ pollution degree II/2

6 kV

Rated impulse voltage for surge voltage  
class/ contamination degree III/3

8 kV

Rated current, min. number of poles  
(Tu=20°C)

57 A

Rated current, min. number of poles  
(Tu=40°C)

41 A

Rated voltage for surge voltage class /  
pollution degree II/2

1,000 V

Rated voltage for surge voltage class /  
pollution degree III/3

800 V

Rated impulse voltage for surge voltage  
class/ pollution degree III/2

8 kV

Short-time withstand current resistance

3 x 1s with 420 A

## Rated data acc. to CSA

Institute (CSA)



Certificate No. (CSA)

200039-1534443

Rated voltage (Use group B / CSA)

600 V

Rated voltage (Use group D / CSA)

600 V

Rated current (Use group C / CSA)

35 A

Wire cross-section, AWG, min.

AWG 24

Reference to approval values

Specifications are  
maximum values, details -  
see approval certificate.

Rated voltage (Use group C / CSA)

600 V

Rated current (Use group B / CSA)

35 A

Rated current (Use group D / CSA)

5 A

Wire cross-section, AWG, max.

AWG 10

## Rated data acc. to UL 1059

Institute (cURus)



Certificate No. (cURus)

E60693

Rated voltage (Use group B / UL 1059)

600 V

Rated voltage (Use group D / UL 1059)

600 V

Rated current (Use group C / UL 1059)

42 A

Wire cross-section, AWG, min.

AWG 24

Reference to approval values

Specifications are  
maximum values, details -  
see approval certificate.

Rated voltage (Use group C / UL 1059)

600 V

Rated current (Use group B / UL 1059)

42 A

Rated current (Use group D / UL 1059)

5 A

Wire cross-section, AWG, max.

AWG 8

## Packing

Packaging

Box

VPE length

110 mm

VPE width

165 mm

VPE height

365 mm

## Type tests

Test: Durability of markings

Standard

DIN EN 61984 section 7.3.2 / 09.02 taking  
pattern from DIN EN 60068-2-70 / 07.96

Test

mark of origin, type identification, pitch, type of  
material

Evaluation

available

Test

durability

Evaluation

passed

**SVZ 7.62HP/04/180SFC SN BK BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data**

|                                              |                |                                                                                    |                              |
|----------------------------------------------|----------------|------------------------------------------------------------------------------------|------------------------------|
| Test: Misengagement (Non-interchangeability) | Standard       | DIN EN 61984 section 6.3 and 6.9.1 / 09.02, DIN EN 60512-13-5 / 11.08              |                              |
|                                              | Test           | 180° turned with coding elements                                                   |                              |
|                                              | Evaluation     | passed                                                                             |                              |
|                                              | Test           | 180° turned without coding elements                                                |                              |
|                                              | Evaluation     | passed                                                                             |                              |
| Test: Clampable cross section                | Standard       | DIN EN 60999-1 section 7 and 9.1 / 12.00, DIN EN 60947-1 section 8.2.4.5.1 / 12.02 |                              |
|                                              | Conductor type | Type of conductor and conductor cross-section                                      | solid 0.5 mm <sup>2</sup>    |
|                                              |                | Type of conductor and conductor cross-section                                      | stranded 0.5 mm <sup>2</sup> |
|                                              |                | Type of conductor and conductor cross-section                                      | solid 6 mm <sup>2</sup>      |
|                                              |                | Type of conductor and conductor cross-section                                      | stranded 6 mm <sup>2</sup>   |
|                                              |                | Type of conductor and conductor cross-section                                      | AWG 24/1                     |
|                                              |                | Type of conductor and conductor cross-section                                      | AWG 24/19                    |
|                                              |                | Type of conductor and conductor cross-section                                      | AWG 10/1                     |
|                                              |                | Type of conductor and conductor cross-section                                      | AWG 10/19                    |
|                                              | Evaluation     | passed                                                                             |                              |

## SVZ 7.62HP/04/180SFC SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                                                           |                |                                               |                              |
|-----------------------------------------------------------|----------------|-----------------------------------------------|------------------------------|
| Test for damage to and accidental loosening of conductors | Standard       | DIN EN 60999-1 section 7 and 9.1 / 12.00      |                              |
|                                                           | Requirement    | 0.2 kg                                        |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section | AWG 24/1                     |
|                                                           |                | Type of conductor and conductor cross-section | AWG 24/19                    |
|                                                           | Evaluation     | passed                                        |                              |
|                                                           | Requirement    | 0.3 kg                                        |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section | solid 0.5 mm <sup>2</sup>    |
|                                                           |                | Type of conductor and conductor cross-section | stranded 0.5 mm <sup>2</sup> |
|                                                           | Evaluation     | passed                                        |                              |
|                                                           | Requirement    | 1.4 kg                                        |                              |
| Pull-out test                                             | Conductor type | Type of conductor and conductor cross-section | solid 6 mm <sup>2</sup>      |
|                                                           |                | Type of conductor and conductor cross-section | stranded 6 mm <sup>2</sup>   |
|                                                           | Conductor type | Type of conductor and conductor cross-section | AWG 10/1                     |
|                                                           |                | Type of conductor and conductor cross-section | AWG 10/19                    |
|                                                           | Evaluation     | passed                                        |                              |
|                                                           | Standard       | DIN EN 60999-1 section 9.5 / 12.00            |                              |
|                                                           | Requirement    | ≥10 N                                         |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section | AWG 24/1                     |
|                                                           |                | Type of conductor and conductor cross-section | AWG 24/19                    |
|                                                           | Evaluation     | passed                                        |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section | solid 0.5 mm <sup>2</sup>    |
|                                                           |                | Type of conductor and conductor cross-section | stranded 0.5 mm <sup>2</sup> |
|                                                           | Evaluation     | passed                                        |                              |
|                                                           | Requirement    | ≥20 N                                         |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section | solid 6 mm <sup>2</sup>      |
|                                                           |                | Type of conductor and conductor cross-section | stranded 6 mm <sup>2</sup>   |
|                                                           | Conductor type | Type of conductor and conductor cross-section | AWG 10/1                     |
|                                                           |                | Type of conductor and conductor cross-section | AWG 10/19                    |
|                                                           | Evaluation     | passed                                        |                              |
|                                                           | Requirement    | ≥80 N                                         |                              |

## SVZ 7.62HP/04/180SFC SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002638    | ETIM 7.0    | EC002638    |
| ECLASS 9.0  | 27-44-03-09 | ECLASS 9.1  | 27-44-03-09 |
| ECLASS 10.0 | 27-44-03-09 | ECLASS 11.0 | 27-46-02-02 |

## Important note

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.                                                                                                                                                                                                                                                                                                                     |
| Notes          | <ul style="list-style-type: none"> <li>• Additional colours on request</li> <li>• Rated current related to rated cross-section &amp; min. No. of poles.</li> <li>• Wire end ferrule without plastic collar to DIN 46228/1</li> <li>• Wire end ferrule with plastic collar to DIN 46228/4</li> <li>• P on drawing = pitch</li> <li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li> <li>• Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months</li> </ul> |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

## Downloads

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a> |
| Engineering Data                            | <a href="#">STEP</a>                            |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                    |
| User Documentation                          | <a href="#">QR-Code product handling video</a>  |


## SVZ 7.62HP/04/180SFC SN BK BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Dimensional drawing



### Graph



### Graph

