

IE-PI-2LC-MM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

FO LC inserts for plug-in connectors ver.1 / 4 / 14

General ordering data

Version	LC insert, Plug insert 2 LC, multimode
Order No.	1962780000
Type	IE-PI-2LC-MM
GTIN (EAN)	4032248644865
Qty.	10 pc(s).

IE-PI-2LC-MM

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	59 mm	Depth (inches)	2.323 inch
Height	10.3 mm	Height (inches)	0.406 inch
Net weight	21.4 g	Width	13.15 mm
Width (inches)	0.518 inch		

Temperatures

Operating temperature	-40 °C...70 °C	Humidity	0...85 % rel. humidity
-----------------------	----------------	----------	------------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Colour	Miscellaneous	Configuration	Connector and flange insert for variant 1, 4 and 14 housings
Connection 1	LC	Connection 2	Crimp
Description of article	Plug insert 2 LC, multimode	Ferrule material	Zirconia
Fibre type	Multimode	Housing main material	PBT diecast zinc
Humidity	0...85 % rel. humidity	Insertion loss	≤ 0.4 dB
Plugging cycles	1000	Protection degree	IP67 with housing
Return loss (attenuation)	≥ 30 dB		

General standards

Connector standard	IEC 61754-20
--------------------	--------------

Classifications

ETIM 6.0	EC001122	ETIM 7.0	EC001122
ECLASS 9.0	19-17-01-22	ECLASS 9.1	19-17-01-22
ECLASS 10.0	19-17-01-22	ECLASS 11.0	19-17-01-22

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	GOST Approval
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN Designation key / Type key

IE-PI-2LC-MM

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

