

IE-PS-V05M-RJ45-TH**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

HDC plug-in connector set according to IEC 61076-3-106
ver.5 in metal, with RJ45 insert

General ordering data

Version	RJ45 crimp plug, Variant 5, Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
Order No.	1963110000
Type	IE-PS-V05M-RJ45-TH
GTIN (EAN)	4032248651610
Qty.	10 pc(s).

Creation date March 26, 2021 3:37:32 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-PS-V05M-RJ45-TH

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	83.28 g
------------	---------

Temperatures

Operating temperature	-40 °C...70 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Connection 1	RJ45	Connection 2	Crimp
Description of article	Variant 5	Housing main material	diecast aluminium
Insulation cross-section, min.	0.85 mm	Insulation cross-section, max.	1.05 mm
Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)	Contact surface	Gold over nickel
Connection diameter, solid	0.36...0.51 mm	Wire connection diameter, solid, min.	0.36 mm
Conductor connection cross-section, solid (AWG)	AWG 26/1...AWG 24/1	Wire connection diameter, solid, max.	0.51 mm
Connection diameter, flexible	0.46...0.61 mm	Wire cross-section, solid, min. (AWG)	AWG 26/1
Wire cross-section, solid, max. (AWG)	AWG 24/1	Conductor connection cross-section, flexible (AWG)	AWG 27/7...AWG 24/7
Wire connection diameter, flexible, min.	0.46 mm	Wire connection diameter, flexible, max.	0.61 mm
Wire cross-section, finely stranded, min. (AWG)	AWG 27/7	Wire cross-section, finely stranded, max. (AWG)	AWG 24/7
MICE classification M	M ₃	MICE classification I	I ₃
MICE classification C	C ₁	MICE classification E	E ₃
Sheath diameter, min.	5 mm	Sheath diameter, max.	12 mm
Shielding	360° all-round enclosure	Protection degree	IP67
Plugging cycles	750		

General standards

Certificate no. (cULus)	E316369	Connector standard	IEC 61076-3-106 Var. 5, IEC 60603-7-51
-------------------------	---------	--------------------	--

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Approvals

Approvals



ROHS	Conform
UL File Number Search	E316369

IE-PS-V05M-RJ45-TH

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Conformity	GOST Approval ISO/IEC EN and TIA/EIA Screened Class EA Category 6A, 4 connector channel DUXR.E316369
Engineering Data	STEP
Engineering Data	WSCAD
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN Manual

IE-PS-V05M-RJ45-TH

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

