

IE-PS-V04P-2LC-SM-BP**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

PushPull plug-in connector set according to IEC
61076-3-106 ver.4 (IEC24702), plastic with LC insert

General ordering data

Version	FO connector, Variant 4, LC-Duplex single-mode, with kink prevention, IP67
Order No.	1963350000
Type	IE-PS-V04P-2LC-SM-BP
GTIN (EAN)	4032248651825
Qty.	10 pc(s).

Creation date March 26, 2021 3:39:22 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-PS-V04P-2LC-SM-BP

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	126.3 mm	Depth (inches)	4.972 inch
Height	20.1 mm	Height (inches)	0.791 inch
Net weight	43.1 g	Width	20.2 mm
Width (inches)	0.795 inch		

Temperatures

Operating temperature	-40 °C...70 °C
-----------------------	----------------

General data

Colour	Miscellaneous	Connection 1	LC
Connection 2		Description of article	Variant 4, LC-Duplex single-mode, with kink prevention
	gluing, crimping, polishing		
Fibre type	Singlemode	Housing main material	PA UL 94 V0
Housing material, insert		Insertion loss	0.5 dB singlemode, 0.4 dB multimode
	PBT, Zinc diecast		
Plugging cycles	500	Protection degree	IP67
Return loss (attenuation)	40 dB singlemode; 30 dB multimode	Sheath diameter, max.	10 mm
Sheath diameter, min.	5 mm		

General standards

Connector standard	IEC 61076-3-106 Var. 4, IEC 61754-20
--------------------	---

Classifications

ETIM 6.0	EC001122	ETIM 7.0	EC001122
ECLASS 9.0	19-17-01-22	ECLASS 9.1	19-17-01-22
ECLASS 10.0	19-17-01-22	ECLASS 11.0	19-17-01-22

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	GOST Approval
Engineering Data	WSCAD
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN Designation key / Type key

IE-PS-V04P-2LC-SM-BP

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

