

IE-PM-RJ45-TH**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

RJ45 crimp plug-in connector according to IEC
60603-7-51 for wire outer diameters up to 1.05 mm

General ordering data

Version	RJ45 crimp plug, Plug without bending protection sleeve, Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
Order No.	1963580000
Type	IE-PM-RJ45-TH
GTIN (EAN)	4032248645688
Qty.	100 pc(s).

IE-PM-RJ45-TH

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	3.46 g
------------	--------

Temperatures

Operating temperature	-40 °C...70 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Connection 1	RJ45	Connection 2	IDC
Description of article		Configuration	Connects piercing contacts and shielded connections in one step, retro-fit for kink-prevention sleeves, Multi-port compatible
	Plug without bending protection sleeve		
Colour	Miscellaneous	Housing main material	Brass, PC UL 94 V0
Insulation cross-section, min.	0.85 mm	Insulation cross-section, max.	1.05 mm
Cable pull-out force, min.		Category	Cat.6A / Class EA (ISO/IEC 11801 2010)
	89 N	Contact surface	Gold-plated
Contact material	Phosphorus bronze	Wire connection diameter, solid, min.	0.36 mm
Connection diameter, solid	0.36...0.51 mm	Wire connection diameter, solid, max.	0.51 mm
Conductor connection cross-section, solid (AWG)	AWG 27...AWG 24	Wire cross-section, solid, min. (AWG)	AWG 27
Connection diameter, flexible	0.46...0.61 mm	Conductor connection cross-section, flexible (AWG)	AWG 27...AWG 24
Wire cross-section, solid, max. (AWG)	AWG 24	Wire connection diameter, flexible, max.	0.61 mm
Wire connection diameter, flexible, min.	0.46 mm	Wire cross-section, finely stranded, max. (AWG)	AWG 24
Wire cross-section, finely stranded, min. (AWG)	AWG 27	MICE classification I	I ₁
MICE classification M	M ₁	MICE classification E	E ₃
MICE classification C	C ₁	Shielding material	0.5 mm brass, 2 µm nickel
Sheath diameter, min.	5 mm	Protection degree	IP20
Bending protection sleeve material	Polycarbonate PC, UL 94 V-0	Material insulator	Polycarbonate PC, UL 94 V-0
Shielding	360° all-round enclosure		
Plugging cycles	750		

Electrical properties

Contact resistance	≤ 20 mΩ	Current-carrying capacity at 50 °C	1 A
Dielectric strength, contact / contact	≤ 1000 V DC	Dielectric strength, contact / shield	≤ 1500 V DC
Insulation strength	500 MΩ	PoE / PoE+	conforming to IEEE 802.3af

General standards

Certificate No. (cURus)	E316369	Connector standard	IEC 60603-7-51
-------------------------	---------	--------------------	----------------

IE-PM-RJ45-TH

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Approvals

Approvals



ROHS	Conform
UL File Number Search	E316369

Downloads

Approval/Certificate/Document of Conformity	GOST Approval ISO/IEC EN and TIA/EIA Screened Class EA Category 6A, 4 connector channel C-Link IE-PS-RJ45-TH-BK UL Approval
Engineering Data	WSCAD
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN Manual

IE-PM-RJ45-TH

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

