

IE-KO-HAT**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

- Overpressure valve protects against overloading
- Cylinder head angled at 90°
- Angled head can be rotated through 360°
- Ergonomic handle springs back automatically
- The waste piece no longer becomes jammed thanks to triple splitting
- Hydraulic punch made of high-strength aluminium (approx. 40% weight saving)
- Service life greatly reduced when stainless steel sheets are used

General ordering data

Version	Sheet holes
Order No.	1966810000
Type	IE-KO-HAT
GTIN (EAN)	4032248659630
Qty.	1 pc(s).

IE-KO-HAT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	70 mm	Depth (inches)	2.756 inch
Height	120 mm	Height (inches)	4.724 inch
Net weight	3,262 g	Weight	1.9 kg
Width	290 mm	Width (inches)	11.417 inch

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Description of article	Hydraulic sheet holes
------------------------	-----------------------

Cutting tools

Max. operating pressure	650 bar	Punching force	75 kN
Rectangular holes up to	36 x 112 mm; 2,0 mm F = 370 N/mm ²	Round holes from 1 to Ø 85 mm	2,0 mm F = 370 N/mm ²
Round holes from 2 to Ø 64 mm	3,0 mm F = 370 N/mm ²	Round holes from 3 to Ø 64 mm	2,5 mm F = 600 N/mm ²
Square holes up to	68 x 68 mm; 2,0 mm F = 370 N/mm ²		

Classifications

ETIM 6.0	EC000156	ETIM 7.0	EC000156
ECLASS 9.0	21-04-90-47	ECLASS 9.1	21-04-90-47
ECLASS 10.0	21-04-90-47	ECLASS 11.0	21-04-51-16

Downloads

User Documentation	Manual
--------------------	------------------------

IE-KO-HAT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

Example of use

