

# Duo spiral plastic tubing PUN-12X2-S-2-DUO-BS

Part number: 197630

FESTO



 General operating condition

## Data sheet

| Feature                                  | Value                                         |
|------------------------------------------|-----------------------------------------------|
| Working length                           | 2 m                                           |
| Outside diameter                         | 12 mm                                         |
| Block length                             | 0.704 m                                       |
| Inside diameter                          | 8 mm                                          |
| Winding diameter                         | 95 mm                                         |
| Number of windings                       | 20                                            |
| Temperature-dependent operating pressure | -0.095 MPa ... 1 MPa                          |
| Temperature-dependent operating pressure | -0.95 bar ... 10 bar                          |
| Temperature-dependent operating pressure | -13.775 psi ... 145 psi                       |
| Certification                            | German Technical Control Board (TÜV)          |
| Certificate issuing authority            | B 013277 0506 00                              |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| LABS (PWIS) conformity                   | VDMA24364-B2-L                                |
| Ambient temperature                      | -35 °C ... 60 °C                              |
| Product weight                           | 830 g                                         |
| Pneumatic connection                     | For plug connection outside diameter 12 mm    |
| Color                                    | Blue/black                                    |
| Shore hardness                           | D 52 +/-3                                     |
| Material of pneumatic tubing             | TPE-U(PU)                                     |