

SAI-M23-KBC-0.08/0.56**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Drawing**

The M23 round plug-in connectors offer a high number of mating cycles, high current-carrying capacity and high contact-density coupled with minimum dimensions. Enclosures, inserts and crimp contacts need to be ordered separately.

General ordering data

Version	Sensor/Actuator plug-in connector, Crimp contact
Order No.	1995860000
Type	SAI-M23-KBC-0.08/0.56
GTIN (EAN)	4032248926152
Qty.	50 pc(s).

SAI-M23-KBC-0.08/0.56

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	0.336 g
------------	---------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Settings re. SAI M23 crimping tool

Settings regarding SAI M23 crimping tool	Crimping mandrel adjustment acc. to mm ²	Wire cross-section	0.14 mm ²
		Crimping mandrel adjustment	0.75
		Wire cross-section	0.25 mm ²
		Crimping mandrel adjustment	0.8
	Crimping Tool	1	
	Locator position	12	
	Crimp contact	Crimpbuchse Signal 1 mm (0,08-0,56 mm ²)	

Technical data customisable plug-in connectors

Conductor cross-section, max.	0.56 mm ²	Conductor cross-section, min.	0.08 mm ²
Contact surface	Gold-plated	Insulation strength	> 10 ¹⁰ Ω
Plugging cycles	> 1000	Type of connection	Crimp connection

Classifications

ETIM 6.0	EC000796	ETIM 7.0	EC000796
ECLASS 9.0	27-44-02-92	ECLASS 9.1	27-44-02-90
ECLASS 10.0	27-44-02-92	ECLASS 11.0	27-44-02-92

Important note

Product information	Enclosures, inserts and crimp contacts need to be ordered separately.
---------------------	---

Approvals

Approvals



ROHS	Conform
UL File Number Search	E344862

Downloads

Engineering Data	STEP
------------------	----------------------