

MLFB-Ordering data 1FG1501-1RE32-2HB1-Z
D11+G23+K07+N23




Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Gearbox data


Gear box type	B29	Radial force maximum	2690 N
Gearbox basic type	Bevel geared	Max. permissible radial force with Mmax	2490 N
Gearbox size	29	Moment of inertia	0.82 kgcm ²
Transmission stages	2	Torsional stiffness	10 Nm/°
Transmission (ratio)	4.21	Efficiency	0.95
Gear number relation	644/153	Mounting position	M1-A
Output moment maximum (short-time)	96 Nm	Mounting type	Housing flange (C type)
max. input speed (briefly)	4500 rpm	Output shaft version	Solid shaft standard
Output speed short-time	1069 rpm	Output shaft dimension	V20x40 mm
Emergency off output moment (1000 cycles)	125 Nm	Gearbox flange diameter	-/-
		Output shaft bearing	No
		Figure 2 torque support	-

General tech. specifications

Degree of protection	IP65
Color of the housing	Standard painting (Anthracite RAL 7016)
Specification	CE / UL / CSA / EAC / cRUus
Net weight	18.53 kg
1m-sound pressure level L _{pA} (Tol.+3dB(A))	70
Plug position	top (default) (2)
Adapter flange position	top (default) (2)

Lubrication and sealing

Gear oil	Polyglycol oil CLP ISO PG VG220
Output shaft sealing	Seal longer service life
Oil charge	0.25 l



SIEMENS

Data sheet for SIMOTICS S-1FG1

MLFB-Ordering data 1FG1501-1RE32-2HB1-Z
D11+G23+K07+N23



Figure similar

Motor data		Limiting data	
Motor type	Permanent-magnet synchronous motor	Maximum speed (short-time)	7200 rpm
Motor type	Compact	Maximum torque	35.00 Nm
DC-link voltage, max.	510...720V	Motor current short term	18.5 A
Shaft height	63 mm	Optimum operating point	
Cooling	Natural cooling	Optimum speed	2000 rpm
Rated speed	2000 rpm	Optimum power	1.67 kW
Rated torque (100K)	8.00 Nm	Recommended Motor Module	
Rated power	1.68 kW	Rated inverter current	5.0 A
Rated current (100K)	4.10 A	Maximum inverter current	15.0 A
Static torque	10.10 Nm	Maximum torque	29.5 Nm
Static current	4.90 A	Holding brake	
Moment of inertia	15.70000 kgcm ²	Holding brake	with holding brake
Efficiency η	91 %	Holding brake version	Permanent-magnet brake
Temperature monitoring	Pt1000 temperature sensor	Power supply voltage	DC 24 V $\pm$ 10 %
Connector size	1	Braking torque M_{1Br} / M_{2Br}	8.50 Nm
Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)	Holding torque M_{4Br}	13.00 Nm
		Opening time	100.0 ms
		Closing time	50.0 ms
		Maximum switching energy per braking action	380.0 J

Info servo geared motor

Outside the standard temperature range of -10 to +40 °C, further selectable options must be observed, in addition to the lubricant selection.

Further, you have to check the suitability of the components and options used for the requested temperature range.

SIEMENS

Data sheet for SIMOTICS S-1FG1

MLFB-Ordering data 1FG1501-1RE32-2HB1-Z
D11+G23+K07+N23




Figure similar

Options		Standards	
D11	M1-A for bevel and worm gearboxes	Compliance with standards	CE / UL / CSA / EAC / cRUus
G23	Seal longer service life		
K07	Polyglycol oil CLP ISO PG VG220		
N23	Standard holding brake (permanent magnet brake)	CE marking	EN 60034