

Data sheet for SIMOTICS S-1FG1

Article No. : 1FG1501-5QC26-2DU1-Z
D12+G23+K07+N23

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :





Figure similar

Gearbox data	
Gear box type	B29
Gearbox basic type	Bevel geared B / K
Gearbox size	29
Transmission stages	2
Transmission (ratio)	25.56
Gear number relation	230/9
Output moment maximum (short-time)	106 Nm
max. input speed (briefly)	4,500 rpm
Output speed short-time	176 rpm
Emergency off output moment (1000 cycles)	187 Nm
Radial force maximum	4,130 N
Max. permissible radial force with Mmax	4,110 N
Moment of inertia	0.11 kgcm ²
Torsional stiffness	13 Nm/°
Efficiency	0.93
Mounting position	M2-A
Mounting type	Torque plate
Output shaft version	Hollow shaft standard
Output shaft dimension	H20 mm
Gearbox flange diameter	-/-
Output shaft bearing	No
Figure 2 torque support	1

General tech. specifications	
Color of the housing	Standard painting (Anthracite RAL 7016)
Specification	CE / UL / CSA / EAC / cRUus
Net weight	8.76 kg
1m-sound pressure level L _{pA} (Tol.+3dB(A))	65
Plug position	top (default) (2)
Adapter flange position	top (default) (2)

Lubrication and sealing	
Gear oil	Polyglycol oil CLP ISO PG VG220
Output shaft sealing	Seal longer service life
Oil charge	0.55 l



Motor data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
DC-link voltage, max.	510...720V
Shaft height	36 mm
Cooling	Natural cooling
Rated speed	6,000 rpm
Rated torque (100K)	0.65 Nm
Rated power	0.41 kW
Rated current (100K)	1.09 A
Static torque	1.01 Nm
Static current	1.50 A
Moment of inertia	0.75000 kgcm ²
Efficiency η	87 %
Temperature monitoring	Pt1000 temperature sensor
Connector size	1
Degree of protection	IP65
Encoder system	Encoder AS20DQI: absolute encoder single-turn 20 bits

Limiting data	
Maximum speed (short-time)	10,000 rpm
Maximum torque	4.50 Nm
Motor current short term	7.0 A

Optimum operating point	
Optimum speed	6,000 rpm
Optimum power	0.41 kW

Data sheet for SIMOTICS S-1FG1

Article No. : 1FG1501-5QC26-2DU1-Z
D12+G23+K07+N23

Recommended Motor Module

Rated inverter current	3.0 A
Maximum inverter current	9.0 A
Maximum torque	4.5 Nm

Holding brake

Holding brake	with holding brake
Holding brake version	Permanent-magnet brake
Power supply voltage	DC 24 V $\pm$ 10 %
Dynamic braking torque M_{1Br}	1.00 Nm
Holding torque M_{4Br}	1.90 Nm
Opening time	50.0 ms
Closing time	30.0 ms
Maximum switching energy per braking action	40.0 J

Standards

Compliance with standards	CE / UL / CSA / EAC / cRUus
CE marking	EN 60034

Options

D12	M2-A for bevel and worm gearboxes
G23	Seal longer service life
K07	Polyglycol oil CLP ISO PG VG220
N23	Standard holding brake (permanent magnet brake)

Info servo geared motor

Outside the standard temperature range of -10 to +40 °C, further selectable options must be observed, in addition to the lubricant selection.

Further, you have to check the suitability of the components and options used for the requested temperature range.