

MLFB-Ordering data1FK7043-7AK71-1UH0



Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	6000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Motor type	High Dynamic
Rated torque (100 K)	2.0 Nm	Shaft height	48
Rated current	4.4 A	Cooling	Natural cooling
Static torque (60 K)	2.50 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	3.10 Nm	Concentricity tolerance	0.08 mm
Stall current (60 K)	4.80 A	Axial runout tolerance	0.08 mm
Stall current (100 K)	6.40 A	Vibration severity grade	Grade A
Moment of inertia	1.140 kgcm²	Connector size	1
Efficiency	90.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.48 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	32.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.65 Ω	Color of the housing	without
Rotating field inductance	9.0 mH	Holding brake	with holding brake
Electrical time constant	13.80 ms	Shaft end	Plain shaft
Mechanical time constant	0.85 ms	Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)
Thermal time constant	40 min		
Shaft torsional stiffness	11000 Nm/rad		
Net weight of the motor	7.0 kg		

MLFB-Ordering data 1FK7043-7AK71-1UH0

Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	9 A
Optimum power	1.3 kW	Maximum inverter current	18 A
Limiting data		Maximum torque	8.50 Nm
Max. permissible speed (mech.)	8000 rpm		
Max. permissible speed (inverter)	13300 rpm		
Maximum torque	9.4 Nm		
Maximum current	20.0 A		
Holding brake			
Holding brake version	Permanent-magnet brake		
Holding torque	4.0 Nm		
Power supply voltage	DC 24 V ± 10 %		
Coil current	0.5 A		
Opening time	70 ms		
Closing time	30 ms		
Highest braking work	150 J		