

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7062-2AC71-1RG1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data																					
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor																				
Number of poles	8	Motor type	Compact																				
Rated torque (100 K)	7.0 Nm	Shaft height	63																				
Rated current	2.6 A	Cooling	Natural cooling																				
Static torque (60 K)	7.10 Nm	Radial runout tolerance	0.040 mm																				
Static torque (100 K)	8.5 Nm	Concentricity tolerance	0.10 mm																				
Stall current (60 K)	2.45 A	Axial runout tolerance	0.10 mm																				
Stall current (100 K)	3.00 A	Vibration severity grade	Grade A																				
Moment of inertia	11.200 kgcm ²	Connector size	1																				
Efficiency	90.0 %	Degree of protection	IP65																				
<table border="1"> <thead> <tr> <th colspan="2">Physical constants</th> </tr> </thead> <tbody> <tr> <td>Torque constant</td> <td>2.83 Nm/A</td> </tr> <tr> <td>Voltage constant at 20° C</td> <td>180.5 V/1000*min⁻¹</td> </tr> <tr> <td>Winding resistance at 20° C</td> <td>3.59 Ω</td> </tr> <tr> <td>Rotating field inductance</td> <td>45.5 mH</td> </tr> <tr> <td>Electrical time constant</td> <td>12.70 ms</td> </tr> <tr> <td>Mechanical time constant</td> <td>1.51 ms</td> </tr> <tr> <td>Thermal time constant</td> <td>35 min</td> </tr> <tr> <td>Shaft torsional stiffness</td> <td>37000 Nm/rad</td> </tr> <tr> <td>Net weight of the motor</td> <td>9.1 kg</td> </tr> </tbody> </table>		Physical constants		Torque constant	2.83 Nm/A	Voltage constant at 20° C	180.5 V/1000*min ⁻¹	Winding resistance at 20° C	3.59 Ω	Rotating field inductance	45.5 mH	Electrical time constant	12.70 ms	Mechanical time constant	1.51 ms	Thermal time constant	35 min	Shaft torsional stiffness	37000 Nm/rad	Net weight of the motor	9.1 kg	Design acc. to Code I	IM B5 (IM V1, IM V3)
		Physical constants																					
		Torque constant	2.83 Nm/A																				
		Voltage constant at 20° C	180.5 V/1000*min ⁻¹																				
		Winding resistance at 20° C	3.59 Ω																				
		Rotating field inductance	45.5 mH																				
		Electrical time constant	12.70 ms																				
		Mechanical time constant	1.51 ms																				
		Thermal time constant	35 min																				
		Shaft torsional stiffness	37000 Nm/rad																				
Net weight of the motor	9.1 kg																						
Temperature monitoring	Pt1000 temperature sensor	Electrical connectors	Connectors for signals and power rotatable																				
Color of the housing	Standard (Anthracite RAL 7016)	Holding brake	without holding brake																				
Shaft extension	Plain shaft	Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)																				



Figure similar

MLFB-Ordering data

1FK7062-2AC71-1RG1

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	3 A
Optimum power	1.5 kW	Maximum inverter current	9 A
Limiting data		Maximum torque	22.90 Nm
Max. permissible speed (mech.)	7200 rpm		
Max. permissible speed (inverter)	3200 rpm		
Maximum torque	26.0 Nm		
Maximum current	10.9 A		