



Figure similar

MLFB-Ordering data 1FK7062-2AF71-1CG1-Z
J32

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	Compact
Rated torque (100 K)	6.0 Nm	Shaft height	63
Rated current	4.0 A	Cooling	Natural cooling
Static torque (60 K)	7.10 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	8.50 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	4.30 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	5.30 A	Vibration severity grade	Grade A
Moment of inertia	13.380 kgcm²	Connector size	1
Physical constants		Degree of protection	IP65
Torque constant	1.60 Nm/A	Design acc. to Code I	IM B5 (IM V1, IM V3)
Voltage constant at 20° C	102.5 V/1000*min ⁻¹	Temperature monitoring	Pt1000 temperature sensor
Winding resistance at 20° C	1.15 Ω	Electrical connectors	Connectors for signals and power rotatable
Rotating field inductance	14.6 mH	Color of the housing	Standard (Anthracite RAL 7016)
Electrical time constant	12.80 ms	Holding brake	without holding brake
Mechanical time constant	1.49 ms	Shaft end	Plain shaft
Thermal time constant	35 min	Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Shaft torsional stiffness	37000 Nm/rad		
Net weight of the motor	17.0 kg		
Recommended Motor Module			
Rated inverter current	5 A		
Maximum inverter current	15 A		
Maximum torque	22.10 Nm		



Figure similar

MLFB-Ordering data 1FK7062-2AF71-1CG1-Z
J32

Gearbox data			
Gearbox type	Planetary gearbox SP+	Moment of inertia of gearbox	2.180 kgcm²
Designation	SP 100S-MF2	Radial output shaft loading, max.	6600 N
Gearbox shaft end	Without feather key	Axial output shaft load, max.	5650 N
Gear ratio + steps	16 (2-step)	Efficiency of gearbox	0.94
Motor speed S3-60 %	6500 rpm	Torsional backlash	5 '
Motor speed S1	3100 rpm	Gearbox weight	7.90 kg
Output torque S1	243 Nm		

Rated output torque at duty type S3-60 % 347 Nm

Limiting data	
Max. permissible speed (mech.)	7200 rpm
Max. permissible speed (inverter)	5600 rpm
Maximum torque	26.0 Nm
Maximum current	19.2 A

Special design	
J32	Mounting of SP+ planetary gearbox