

Article No. : 1FK7062-2AF71-1CH1-Z
J23

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data	
Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	6.0 Nm
Rated current	4.0 A
Static torque (60 K)	7.10 Nm
Static torque (100 K)	8.50 Nm
Stall current (60 K)	4.30 A
Stall current (100 K)	5.30 A
Moment of inertia	14.810 kgcm ²

Physical constants	
Torque constant	1.60 Nm/A
Voltage constant at 20° C	102.5 V/1000*min ⁻¹
Winding resistance at 20° C	1.15 Ω
Rotating field inductance	14.6 mH
Electrical time constant	12.80 ms
Mechanical time constant	1.49 ms
Thermal time constant	35 min
Shaft torsional stiffness	26,500 Nm/rad
Net weight of the motor	18.2 kg

Recommended Motor Module	
Rated inverter current	5 A
Maximum inverter current	15 A
Maximum torque	22.10 Nm

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Gearbox data	
Gearbox type	Planetary gearbox SP+
Designation	SP 100S-MF1
Gearbox shaft end	Without feather key
Gear ratio + steps	5 (1-step)
Motor speed S3-60 %	5,500 rpm
Motor speed S1	2,500 rpm
Output torque S1	169 Nm
Rated output torque at duty type S3-60 %	378 Nm
Moment of inertia of gearbox	2.610 kgcm ²
Radial output shaft loading, max.	6,600 N
Axial output shaft load, max.	5,650 N
Efficiency of gearbox	0.97
Torsional backlash	3 ´
Gearbox weight	7.70 kg

Limiting data	
Max. permissible speed (mech.)	7,200 rpm
Max. permissible speed (inverter)	5,600 rpm
Maximum torque	26.0 Nm
Maximum current	19.2 A

Data sheet for SIMOTICS S-1FK7 servo geared motor

Article No. : 1FK7062-2AF71-1CH1-Z
J23



Figure similar

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	13.0 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.8 A
Opening time	100 ms
Closing time	50 ms
Highest braking work	380 J

Special design	
----------------	--

J23 Mounting of SP+ planetary gearbox