



Figure similar

MLFB-Ordering data 1FK7062-3BF71-1CH1-Z
J02

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	High Inertia
Rated torque (100 K)	6.0 Nm	Shaft height	63
Rated current	4.0 A	Cooling	Natural cooling
Static torque (60 K)	7.10 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	8.5 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	4.30 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	5.30 A	Vibration severity grade	Grade A
Moment of inertia	27.540 kgcm ²	Connector size	1
Physical constants		Degree of protection	IP65
Torque constant	1.60 Nm/A	Design acc. to Code I	IM B5 (IM V1, IM V3)
Voltage constant at 20° C	102.5 V/1000*min ⁻¹	Temperature monitoring	Pt1000 temperature sensor
Winding resistance at 20° C	1.15 Ω	Electrical connectors	Connectors for signals and power rotatable
Rotating field inductance	14.6 mH	Color of the housing	Standard (Anthracite RAL 7016)
Electrical time constant	12.80 ms	Holding brake	with holding brake
Mechanical time constant	3.15 ms	Shaft extension	Plain shaft
Thermal time constant	35 min	Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Shaft torsional stiffness	25000 Nm/rad		
Net weight of the motor	19.8 kg		
Recommended Motor Module			
Rated inverter current	5 A		
Maximum inverter current	15 A		
Maximum torque	22.10 Nm		



Figure similar

MLFB-Ordering data 1FK7062-3BF71-1CH1-Z
J02

Gearbox data			
Gearbox type	Planetary gearbox SP+	Moment of inertia of gearbox	3.040 kgcm²
Designation	SP 100S-MF1	Radial output shaft loading, max.	6600 N
Gearbox shaft end	With feather key	Axial output shaft load, max.	5650 N
Gear ratio + steps	4 (1-step)	Efficiency of gearbox	0.97
Motor speed S3-60 %	5500 rpm	Torsional backlash	3 '
Motor speed S1	2500 rpm	Gearbox weight	7.70 kg
Output torque S1	171 Nm		
Rated output torque at duty type S3-60 %	378 Nm		

Limiting data	
Max. permissible speed (mech.)	7200 rpm
Max. permissible speed (inverter)	5600 rpm
Maximum torque	26.0 Nm
Maximum current	19.2 A

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	13.0 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.8 A
Opening time	100 ms
Closing time	50 ms
Highest braking work	380 J

Special design	
J02	Mounting of SP+ planetary gearbox