

Data sheet for SIMOTICS S-1FK7



MLFB-Ordering data 1FK7063-2AC74-1EH0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                                | Mechanical data          |                                                                                                 |
|-----------------------------|--------------------------------|--------------------------|-------------------------------------------------------------------------------------------------|
| Rated speed (100 K)         | 2000 rpm                       | Motor type               | Permanent-magnet synchronous motor                                                              |
| Number of poles             | 8                              | Motor type               | Compact                                                                                         |
| Rated torque (100 K)        | 8.9 Nm                         | Shaft height             | 63                                                                                              |
| Rated current               | 4.4 A                          | Cooling                  | Natural cooling                                                                                 |
| Static torque (60 K)        | 9.10 Nm                        | Radial runout tolerance  | 0.040 mm                                                                                        |
| Static torque (100 K)       | 11.0 Nm                        | Concentricity tolerance  | 0.10 mm                                                                                         |
| Stall current (60 K)        | 4.30 A                         | Axial runout tolerance   | 0.10 mm                                                                                         |
| Stall current (100 K)       | 5.30 A                         | Vibration severity grade | Grade A                                                                                         |
| Moment of inertia           | 15.700 kgcm²                   | Connector size           | 1                                                                                               |
| Efficiency                  | 91.0 %                         | Degree of protection     | IP64                                                                                            |
| Physical constants          |                                | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                                            |
| Torque constant             | 2.08 Nm/A                      | Temperature monitoring   | Pt1000 temperature sensor                                                                       |
| Voltage constant at 20° C   | 136.5 V/1000*min <sup>-1</sup> | Electrical connectors    | Connectors for signals and power rotatable                                                      |
| Winding resistance at 20° C | 1.45 Ω                         | Color of the housing     | Standard (Anthracite RAL 7016)                                                                  |
| Rotating field inductance   | 19.4 mH                        | Holding brake            | with holding brake                                                                              |
| Electrical time constant    | 13.40 ms                       | Shaft extension          | Plain shaft                                                                                     |
| Mechanical time constant    | 1.47 ms                        | Encoder system           | Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface |
| Thermal time constant       | 40 min                         |                          |                                                                                                 |
| Shaft torsional stiffness   | 25000 Nm/rad                   |                          |                                                                                                 |
| Net weight of the motor     | 12.5 kg                        |                          |                                                                                                 |



MLFB-Ordering data                      1FK7063-2AC74-1EH0

| Optimum operating point           |                        | Recommended Motor Module |          |
|-----------------------------------|------------------------|--------------------------|----------|
| Optimum speed                     | 2000 rpm               | Rated inverter current   | 5 A      |
| Optimum power                     | 1.9 kW                 | Maximum inverter current | 15 A     |
| Limiting data                     |                        | Maximum torque           | 29.50 Nm |
| Max. permissible speed (mech.)    | 7200 rpm               |                          |          |
| Max. permissible speed (inverter) | 4200 rpm               |                          |          |
| Maximum torque                    | 35.0 Nm                |                          |          |
| Maximum current                   | 18.5 A                 |                          |          |
| Holding brake                     |                        |                          |          |
| Holding brake version             | Permanent-magnet brake |                          |          |
| Holding torque                    | 13.0 Nm                |                          |          |
| Power supply voltage              | DC 24 V ± 10 %         |                          |          |
| Coil current                      | 0.8 A                  |                          |          |
| Opening time                      | 100 ms                 |                          |          |
| Closing time                      | 50 ms                  |                          |          |
| Highest braking work              | 380 J                  |                          |          |