



Figure similar

Article No. : 1FK7063-2AF71-1UA0-Z
N05

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	7.3 Nm
Rated current	5.6 A
Static torque (60 K)	9.10 Nm
Static torque (100 K)	11.00 Nm
Stall current (60 K)	6.50 A
Stall current (100 K)	8.00 A
Moment of inertia	14.700 kgcm ²
Efficiency	91.0 %

Physical constants	
Torque constant	1.37 Nm/A
Voltage constant at 20° C	90.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.64 Ω
Rotating field inductance	8.5 mH
Electrical time constant	13.40 ms
Mechanical time constant	1.48 ms
Thermal time constant	40 min
Shaft torsional stiffness	34,000 Nm/rad
Net weight of the motor	11.1 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Feather key
Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)

Optimum operating point	
Optimum speed	3,000 rpm
Optimum power	2.3 kW

Limiting data	
Max. permissible speed (mech.)	7,200 rpm
Max. permissible speed (inverter)	6,400 rpm
Maximum torque	35.0 Nm
Maximum current	28.0 A

Recommended Motor Module	
Rated inverter current	9 A
Maximum inverter current	27 A
Maximum torque	34.00 Nm

Special design	
N05	Non-standard shaft end (dimensions as for 1FT5 motors)