



Figure similar

MLFB-Ordering data 1FK7063-2AH71-1CG1-Z
J33+X01

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	Compact
Rated torque (100 K)	3.0 Nm	Shaft height	63
Rated current	3.8 A	Cooling	Natural cooling
Static torque (60 K)	9.10 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	11.00 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	9.70 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	12.00 A	Vibration severity grade	Grade A
Moment of inertia	17.410 kgcm ²	Connector size	1
Physical constants		Degree of protection	IP65
Torque constant	0.92 Nm/A	Design acc. to Code I	IM B5 (IM V1, IM V3)
Voltage constant at 20° C	60.0 V/1000*min ⁻¹	Temperature monitoring	Pt1000 temperature sensor
Winding resistance at 20° C	0.29 Ω	Electrical connectors	Connectors for signals and power rotatable
Rotating field inductance	3.8 mH	Color of the housing	Jet black, matt RAL 9005
Electrical time constant	13.20 ms	Holding brake	without holding brake
Mechanical time constant	1.51 ms	Shaft end	Plain shaft
Thermal time constant	40 min	Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Shaft torsional stiffness	34000 Nm/rad		
Net weight of the motor	28.1 kg		
Recommended Motor Module			
Rated inverter current	18 A		
Maximum inverter current	54 A		
Maximum torque	35.00 Nm		



Figure similar

MLFB-Ordering data 1FK7063-2AH71-1CG1-Z
J33+X01

Gearbox data			
Gearbox type	Planetary gearbox SP+	Moment of inertia of gearbox	2.710 kgcm²
Designation	SP 140S-MF2	Radial output shaft loading, max.	9900 N
Gearbox shaft end	Without feather key	Axial output shaft load, max.	9870 N
Gear ratio + steps	20 (2-step)	Efficiency of gearbox	0.94
Motor speed S3-60 %	6000 rpm	Torsional backlash	5 '
Motor speed S1	2900 rpm	Gearbox weight	17.00 kg
Output torque S1	493 Nm		

Rated output torque at duty type S3-60 % 726 Nm

Special design	
J33	Mounting of SP+ planetary gearbox
X01	Paint finish: Jet black, matt RAL 9005

Limiting data	
Max. permissible speed (mech.)	7200 rpm
Max. permissible speed (inverter)	7200 rpm
Maximum torque	35.0 Nm
Maximum current	42.0 A