

Data sheet for SIMOTICS S-1FK7



MLFB-Ordering data 1FK7064-4CF71-1UB0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Motor type	High Dynamic
Rated torque (100 K)	8.0 Nm	Shaft height	63
Rated current	7.6 A	Cooling	Natural cooling
Static torque (60 K)	10.00 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	12.00 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	8.70 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	10.80 A	Vibration severity grade	Grade A
Moment of inertia	8.500 kgcm²	Connector size	1
Efficiency	93.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	1.11 Nm/A	Temperature monitoring	Pt1000 temperature sensor
Voltage constant at 20° C	70.5 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.35 Ω	Color of the housing	Standard (Anthracite RAL 7016)
Rotating field inductance	12.0 mH	Holding brake	with holding brake
Electrical time constant	34.50 ms	Shaft end	Feather key
Mechanical time constant	0.64 ms	Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)
Thermal time constant	55 min		
Shaft torsional stiffness	22500 Nm/rad		
Net weight of the motor	16.8 kg		



Figure similar

MLFB-Ordering data

1FK7064-4CF71-1UB0

Optimum operating point	
Optimum speed	3000 rpm
Optimum power	2.5 kW
Limiting data	
Max. permissible speed (mech.)	7500 rpm
Max. permissible speed (inverter)	7500 rpm
Maximum torque	32.0 Nm
Maximum current	33.0 A
Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	13.0 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.8 A
Opening time	100 ms
Closing time	50 ms
Highest braking work	380 J

Recommended Motor Module	
Rated inverter current	18 A
Maximum inverter current	54 A
Maximum torque	32.00 Nm