

No image
available for this
configuration.

Figure similar

MLFB-Ordering data 1FK7064-7AH71-1KH0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Motor type	High Dynamic
Rated torque (100 K)	5.0 Nm	Shaft height	63
Rated current	7.0 A	Cooling	Natural cooling
Static torque (60 K)	9.00 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	12.0 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	12.00 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	15.00 A	Vibration severity grade	Grade A
Moment of inertia	6.840 kgcm²	Connector size	1
Efficiency	93.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.77 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	51.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.18 Ω	Color of the housing	without
Rotating field inductance	5.6 mH	Holding brake	with holding brake
Electrical time constant	31.10 ms	Shaft end	Plain shaft
Mechanical time constant	0.59 ms	Encoder system	Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Thermal time constant	55 min		
Shaft torsional stiffness	30000 Nm/rad		
Net weight of the motor	16.8 kg		

MLFB-Ordering data 1FK7064-7AH71-1KH0

Optimum operating point		Recommended Motor Module	
Optimum speed	3500 rpm	Rated inverter current	18 A
Optimum power	2.8 kW	Maximum inverter current	36 A
Limiting data		Maximum torque	28.20 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	11300 rpm		
Maximum torque	32.0 Nm		
Maximum current	42.0 A		
Holding brake			
Holding brake version	Permanent-magnet brake		
Holding torque	13.0 Nm		
Power supply voltage	DC 24 V ± 10 %		
Coil current	0.8 A		
Opening time	100 ms		
Closing time	50 ms		
Highest braking work	380 J		