



Figure similar

MLFB-Ordering data

1FK7081-3BF71-1RG0-Z
V40

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data	
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	High Inertia
Rated torque (100 K)	8.7 Nm	Shaft height	80
Rated current	6.8 A	Cooling	Natural cooling
Static torque (60 K)	10.00 Nm	Radial runout tolerance	0.050 mm
Static torque (100 K)	12.0 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	7.10 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	8.70 A	Vibration severity grade	Grade A
Moment of inertia	57.800 kgcm ²	Connector size	1
Physical constants		Degree of protection	IP64
		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Temperature monitoring	Pt1000 temperature sensor
		Electrical connectors	Connectors for signals and power rotatable
		Color of the housing	Standard (Anthracite RAL 7016)
		Holding brake	without holding brake
		Shaft extension	Plain shaft
		Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Recommended Motor Module			
Rated inverter current	9 A		
Maximum inverter current	27 A		
Maximum torque	34.10 Nm		



Figure similar

MLFB-Ordering data 1FK7081-3BF71-1RG0-Z
V40

Gearbox data			
Gearbox type	Planetary gearbox NP+	Moment of inertia of gearbox	8.800 kgcm²
Designation	NP 045	Radial output shaft loading, max.	8000 N
Gearbox shaft end	With feather key	Axial output shaft load, max.	0 N
Gear ratio + steps	5 (1-step)	Efficiency of gearbox	0.97
Temporary input speed	4000 rpm	Torsional backlash	8 '
Motor speed S1	2000 rpm	Gearbox weight	19.00 kg
Output torque S1	350 Nm		
Output moment maximum (short-time)	500 Nm		

Limiting data	
Max. permissible speed (mech.)	6000 rpm
Max. permissible speed (inverter)	6000 rpm
Maximum torque	37.0 Nm
Maximum current	30.0 A

Special design	
V40	Mounting of NP+ planetary gearbox