

****spare part**** SIMOTICS S synchronous servo geared motor 1FK7 Compact, 3.30 kW naturally cooled power/signal connector plug rotatable by 270° motor with holding brake direct gearbox mounting ABSOLUTE ENCODER (ENDAT) 2048 S/R, WITH DRIVE CLIQ-INTERFACE PERFORMANCE REDUCTION BY 10% DUE TO ABSOLUTE ENCODER; OIL-TIGHT FLANGE FOR MOUNTED GEARING, SPECIAL PAINT CLIMATIC GROUP WORLDWIDE, COLOR RAL 7016 BEVEL GEARING, P2=3.20 KW, N2=177 RPM, M2=173 NM, I=17 TAPPED HOLE CIRCLE, HOLLOW SHAFT WITH FEATHERKEY WAY (PLUG-IN GEAR SIDE 4) DESIGN IM B6, EL4, CONNECTOR POSITION GEAR SIDE 3 Q90: Food-grade gear oil X08: PAINT FINISH WHITE ALUMINIUM RAL 9006

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

