

Article No. : 1FK7083-5AF71-1UG5

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Figure similar



| Engineering data      |                          |
|-----------------------|--------------------------|
| Rated speed (100 K)   | 3,000 rpm                |
| Number of poles       | 8                        |
| Rated torque (100 K)  | 10.5 Nm                  |
| Rated current         | 7.4 A                    |
| Static torque (60 K)  | 13.30 Nm                 |
| Static torque (100 K) | 16.00 Nm                 |
| Stall current (60 K)  | 8.60 A                   |
| Stall current (100 K) | 10.40 A                  |
| Moment of inertia     | 27.300 kgcm <sup>2</sup> |
| Efficiency            | 93.0 %                   |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 1.52 Nm/A                     |
| Voltage constant at 20° C   | 97.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.40 Ω                        |
| Rotating field inductance   | 6.0 mH                        |
| Electrical time constant    | 15.50 ms                      |
| Mechanical time constant    | 1.41 ms                       |
| Thermal time constant       | 50 min                        |
| Shaft torsional stiffness   | 105,000 Nm/rad                |
| Net weight of the motor     | 14.0 kg                       |

| Mechanical data          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                       |
| Motor type               | Compact                                                                  |
| Shaft height             | 80                                                                       |
| Cooling                  | Natural cooling                                                          |
| Radial runout tolerance  | 0.050 mm                                                                 |
| Concentricity tolerance  | 0.10 mm                                                                  |
| Axial runout tolerance   | 0.10 mm                                                                  |
| Vibration severity grade | Grade A                                                                  |
| Connector size           | 1                                                                        |
| Degree of protection     | IP65 and DE flange IP67                                                  |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                     |
| Temperature monitoring   | KTY84 temperature sensor in the stator winding                           |
| Electrical connectors    | Connectors for signals and power rotatable                               |
| Color of the housing     | Standard (Anthracite RAL 7016)                                           |
| Holding brake            | without holding brake                                                    |
| Shaft end                | Plain shaft                                                              |
| Encoder system           | Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole) |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 3,000 rpm |
| Optimum power           | 3.3 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 6,000 rpm |
| Max. permissible speed (inverter) | 5,900 rpm |
| Maximum torque                    | 50.0 Nm   |
| Maximum current                   | 37.0 A    |

| Recommended Motor Module |          |
|--------------------------|----------|
| Rated inverter current   | 9 A      |
| Maximum inverter current | 18 A     |
| Maximum torque           | 27.80 Nm |