

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data 1FK7084-2AC71-1TA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	Compact
Rated torque (100 K)	15.0 Nm	Shaft height	80
Rated current	6.7 A	Cooling	Natural cooling
Static torque (60 K)	16.60 Nm	Radial runout tolerance	0.050 mm
Static torque (100 K)	20.00 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	6.90 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	8.50 A	Vibration severity grade	Grade A
Moment of inertia	32.500 kgcm ²	Connector size	1
Efficiency	93.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	2.36 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	152.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.58 Ω	Color of the housing	Standard (Anthracite RAL 7016)
Rotating field inductance	12.0 mH	Holding brake	without holding brake
Electrical time constant	20.50 ms	Shaft end	Feather key
Mechanical time constant	1.02 ms	Encoder system	Resolver 2-pole
Thermal time constant	55 min		
Shaft torsional stiffness	93000 Nm/rad		
Net weight of the motor	18.3 kg		



MLFB-Ordering data 1FK7084-2AC71-1TA0

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	9 A
Optimum power	3.1 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	58.40 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	3800 rpm		
Maximum torque	61.0 Nm		
Maximum current	28.5 A		