

No image
available for this
configuration.

Figure similar

MLFB-Ordering data1FK7085-7AF71-1DA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	High Dynamic
Rated torque (100 K)	6.5 Nm	Shaft height	80
Rated current	7.0 A	Cooling	Natural cooling
Static torque (60 K)	17.00 Nm	Radial runout tolerance	0.050 mm
Static torque (100 K)	22.0 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	16.50 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	22.50 A	Vibration severity grade	Grade A
Moment of inertia	23.000 kgcm²	Connector size	1.5
Efficiency	92.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.96 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	63.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.12 Ω	Color of the housing	without
Rotating field inductance	3.3 mH	Holding brake	without holding brake
Electrical time constant	27.50 ms	Shaft end	Feather key
Mechanical time constant	0.90 ms	Encoder system	Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits
Thermal time constant	65 min		
Shaft torsional stiffness	83000 Nm/rad		
Net weight of the motor	23.5 kg		

MLFB-Ordering data 1FK7085-7AF71-1DA0

Optimum operating point		Recommended Motor Module	
Optimum speed	2500 rpm	Rated inverter current	30 A
Optimum power	3.1 kW	Maximum inverter current	56 A
Limiting data		Maximum torque	52.60 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	9100 rpm		
Maximum torque	65.0 Nm		
Maximum current	80.0 A		