

Data sheet for SIMOTICS S-1FL6

MLFB-Ordering data 1FL6042-2AF21-1LA1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	3000 rpm	Motor type	Low Inertia
Rated torque (100 K)	2.39 Nm	Motor type	Permanent-magnet synchronous motor
Rated current	4.7 A		
Rated power	0.75 kW / 1.02 hp	Shaft height	40
Max. speed	5000 rpm	Encoder system	Absolute encoder 20 bit + 12 bit multi-turn
Maximum torque	7.20 Nm	Cooling	Natural cooling
Max. current	14.2 A	Shaft end	Feather key
Static torque	2.39 Nm	Radial runout tolerance	Class N
Moment of inertia	0.897 kgcm²	Vibration severity grade	Grade A
Physical constants		Degree of protection	IP65
Torque constant	0.51 Nm/A	Design acc. to Code I	IM B5 (IM V1, IM V3)
Thermal class	B (130 °C)	Connection type	Cable outlet
Net weight	2.80 kg		
Ambient conditions			
Ambient temperature			
Operation	0 ... 40 °C		
Relative humidity			
Max. operation	90 % RH maximum (no condensation at 30 °C)		
Standards			
Compliance with standards	CE, EAC		