

## Data sheet for SIMOTICS S-1FL6

MLFB-Ordering data                      1FL6061-1AC61-2AH1



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data          |                                            | Mechanical data                 |                                            |
|---------------------------|--------------------------------------------|---------------------------------|--------------------------------------------|
| Rated speed               | 2000 rpm                                   | Motor type                      | High Inertia                               |
| Rated torque (100 K)      | 3.58 Nm                                    | Motor type                      | Permanent-magnet synchronous motor         |
| Rated current             | 2.5 A                                      | Shaft height                    | 65                                         |
| Rated power               | 0.75 kW / 1.02 hp                          | Encoder system                  | Incremental encoder TTL, 2500 S/R (13 bit) |
| Max. speed                | 3000 rpm                                   | Cooling                         | Natural cooling                            |
| Maximum torque            | 10.70 Nm                                   | Shaft extension                 | Plain shaft                                |
| Max. current              | 7.5 A                                      | Radial runout tolerance         | Class N                                    |
| Static torque             | 4.00 Nm                                    | Vibration severity grade        | Grade A                                    |
| Moment of inertia         | 9.100 kgcm <sup>2</sup>                    | Degree of protection            | IP65                                       |
| Physical constants        |                                            | Design acc. to Code I           | IM B5 (IM V1, IM V3)                       |
| Torque constant           | 1.50 Nm/A                                  | Connection type                 | Angular connector (rotatable)              |
| Thermal class             | B (130 °C)                                 |                                 |                                            |
| Net weight                | 8.80 kg                                    |                                 |                                            |
| Ambient conditions        |                                            | Holding brake                   |                                            |
| Ambient temperature       |                                            | Holding torque M <sub>4Br</sub> | 12.00 Nm                                   |
| Operation                 | 0 ... 40 °C                                | Rated voltage                   | 24 V DC ±10 %                              |
| Relative humidity         |                                            | Opening time                    | 180 ms                                     |
| Max. operation            | 90 % RH maximum (no condensation at 30 °C) | Closing time                    | 60 ms                                      |
| Standards                 |                                            | Rated current                   | 1.50 A                                     |
| Compliance with standards | CE, EAC                                    |                                 |                                            |