

Data sheet for SIMOTICS S-1FL6

MLFB-Ordering data

1FL6096-1AC61-2AB1



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data	
Rated speed	2000 rpm	Motor type	High Inertia
Rated torque (100 K)	33.40 Nm	Motor type	Permanent-magnet synchronous motor
Rated current	13.2 A	Shaft height	90
Rated power	7.00 kW / 9.52 hp	Encoder system	Incremental encoder TTL, 2500 S/R (13 bit)
Max. speed	2000 rpm	Cooling	Natural cooling
Maximum torque	90.00 Nm	Shaft extension	Feather key
Max. current	35.6 A	Radial runout tolerance	Class N
Static torque	40.00 Nm	Vibration severity grade	Grade A
Moment of inertia	143.200 kgcm ²	Degree of protection	IP65
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	2.70 Nm/A	Connection type	Angular connector (rotatable)
Thermal class	B (130 °C)		
Net weight	39.30 kg		
Ambient conditions		Holding brake	
Ambient temperature		Holding torque M_{4Br}	30.00 Nm
Operation	0 ... 40 °C	Rated voltage	24 V DC ±10 %
Relative humidity		Opening time	220 ms
Max. operation	90 % RH maximum (no condensation at 30 °C)	Closing time	115 ms
Standards		Rated current	1.90 A
Compliance with standards	CE, EAC		