



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7034-1AK71-1CG1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	6,000 rpm
Number of poles	6
Rated torque (100 K)	1.4 Nm
Rated current	2.10 A
Static torque (60 K)	1.6 Nm
Static torque (100 K)	2.0 Nm
Stall current (60 K)	2.20 A
Stall current (100 K)	2.70 A
Rotor moment of inertia	0.85 kgcm²
Efficiency	90.0 %

Physical constants	
Torque constant	0.74 Nm/A
Voltage constant at 20° C	49.0 V/1000*min ⁻¹
Winding resistance at 20° C	2.40 Ω
Rotary field inductance	9.7 mH
Electrical time constant	4.00 ms
Mechanical time constant	1.10 ms
Thermal time constant	25 min
Shaft torsional stiffness	3,700 Nm/rad
Net weight of the motor	3.8 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact core type
Shaft height	36
Cooling	Natural cooling
Radial runout tolerance	0.035 mm
Concentricity tolerance	0.080 mm
Axial runout tolerance	0.080 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Connector turnable
Connector size	1

Optimum operating point	
Optimum speed	6,000 rpm
Optimum power	0.9 kW

Limiting data	
Max. permissible speed (mech.)	10,000 rpm
Max. permissible speed (inverter)	10,000 rpm
Maximum torque	8.0 Nm
Maximum current	12.00 A

Recommended Motor Module	
Rated inverter current	3.00 A
Maximum inverter current	6.00 A