



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7044-5AK71-1NK5

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	6,000 rpm
Number of poles	6
Rated torque (100 K)	2.0 Nm
Rated current	2.50 A
Static torque (60 K)	4.4 Nm
Static torque (100 K)	5.0 Nm
Stall current (60 K)	4.90 A
Stall current (100 K)	5.70 A
Rotor moment of inertia	5.43 kgcm ²
Efficiency	91.0 %

Physical constants

Torque constant	0.89 Nm/A
Voltage constant at 20° C	56.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.61 Ω
Rotary field inductance	4.2 mH
Electrical time constant	7.00 ms
Mechanical time constant	1.30 ms
Thermal time constant	35 min
Shaft torsional stiffness	12,300 Nm/rad
Net weight of the motor	7.2 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.021 mm
Concentricity tolerance	0.040 mm
Axial runout tolerance	0.040 mm
Vibration severity grade	Grade R
Degree of protection	IP67
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track
Electrical connection	Connector turnable
Connector size	1

Optimum operating point

Optimum speed	4,500 rpm
Optimum power	1.4 kW

Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	9,000 rpm
Maximum torque	23.0 Nm
Maximum current	30.00 A

Recommended Motor Module

Rated inverter current	9.00 A
Maximum inverter current	27.00 A
Maximum torque	21.9 Nm