

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7046-5AH70-1MH0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data

Rated speed	4,500 rpm
Number of poles	6
Rated torque (100 K)	2.4 Nm
Rated current	3.20 A
Static torque (60 K)	6.0 Nm
Static torque (100 K)	7.0 Nm
Stall current (60 K)	6.90 A
Stall current (100 K)	8.10 A
Rotor moment of inertia	8.39 kgcm ²
Efficiency	90.0 %

Physical constants

Torque constant	0.87 Nm/A
Voltage constant at 20° C	55.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.41 Ω
Rotary field inductance	2.9 mH
Electrical time constant	7.00 ms
Mechanical time constant	1.20 ms
Thermal time constant	35 min
Shaft torsional stiffness	8,300 Nm/rad
Net weight of the motor	10.2 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.080 mm
Axial runout tolerance	0.080 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (new flange design)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface
Electrical connection	Connector turnable
Connector size	1

Optimum operating point

Optimum speed	3,500 rpm
Optimum power	1.3 kW

Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	9,000 rpm
Maximum torque	31.0 Nm
Maximum current	38.00 A

Recommended Motor Module

Rated inverter current	9.00 A
Maximum inverter current	27.00 A
Maximum torque	22.4 Nm

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	8.0 Nm
Braking torque	5.0 Nm
Power supply voltage	DC 24 V
Coil current	0.60 A
Permissible brake work	270 J
Opening time	90 ms
Closing time	30 ms