

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7066-5AH71-1CL1-Z
X01+Y84

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data	
Rated speed	4,500 rpm
Number of poles	10
Rated torque (100 K)	5.0 Nm
Rated current	6.30 A
Static torque (60 K)	10.0 Nm
Static torque (100 K)	12.0 Nm
Stall current (60 K)	11.30 A
Stall current (100 K)	13.60 A
Rotor moment of inertia	19.30 kgcm ²
Efficiency	90.0 %

Physical constants	
Torque constant	0.88 Nm/A
Voltage constant at 20° C	56.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.20 Ω
Rotary field inductance	2.3 mH
Electrical time constant	12.00 ms
Mechanical time constant	1.20 ms
Thermal time constant	40 min
Shaft torsional stiffness	24,000 Nm/rad
Net weight of the motor	14.1 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.021 mm
Concentricity tolerance	0.050 mm
Axial runout tolerance	0.050 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Jet black, matt RAL 9005
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Connector turnable
Connector size	1

Optimum operating point	
Optimum speed	4,000 rpm
Optimum power	2.5 kW

Limiting data	
Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	8,000 rpm
Maximum torque	49.0 Nm
Maximum current	70.00 A

Recommended Motor Module	
Rated inverter current	18.00 A
Maximum inverter current	54.00 A
Maximum torque	42.8 Nm

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	18.0 Nm
Braking torque	11.0 Nm
Power supply voltage	DC 24 V
Coil current	0.80 A
Permissible brake work	880 J
Opening time	150 ms
Closing time	50 ms

Special design	
X01	Paint finish: Jet black, matt RAL 9005
Y84	Customer specifications on rating plate: