



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7066-5AH71-1BG1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data        |                         |
|-------------------------|-------------------------|
| Rated speed             | 4,500 rpm               |
| Number of poles         | 10                      |
| Rated torque (100 K)    | 5.0 Nm                  |
| Rated current           | 6.30 A                  |
| Static torque (60 K)    | 10.0 Nm                 |
| Static torque (100 K)   | 12.0 Nm                 |
| Stall current (60 K)    | 11.30 A                 |
| Stall current (100 K)   | 13.60 A                 |
| Rotor moment of inertia | 16.40 kgcm <sup>2</sup> |
| Efficiency              | 90.0 %                  |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 0.88 Nm/A                     |
| Voltage constant at 20° C   | 56.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.20 Ω                        |
| Rotary field inductance     | 2.3 mH                        |
| Electrical time constant    | 12.00 ms                      |
| Mechanical time constant    | 1.20 ms                       |
| Thermal time constant       | 40 min                        |
| Shaft torsional stiffness   | 31,500 Nm/rad                 |
| Net weight of the motor     | 12.3 kg                       |

| Mechanical data          |                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                                     |
| Motor type               | Compact                                                                                |
| Shaft height             | 63                                                                                     |
| Cooling                  | Natural cooling                                                                        |
| Radial runout tolerance  | 0.040 mm                                                                               |
| Concentricity tolerance  | 0.100 mm                                                                               |
| Axial runout tolerance   | 0.100 mm                                                                               |
| Vibration severity grade | Grade A                                                                                |
| Degree of protection     | IP65                                                                                   |
| Design acc. to Code I    | IM B5 (compatible with 1FT6)                                                           |
| Temperature monitoring   | Pt1000 temperature sensor                                                              |
| Color of the housing     | Standard (pearl dark gray similar to RAL 9023)                                         |
| Shaft end type           | Plain shaft                                                                            |
| Sensor design            | Encoder AS24DQI: Absolut encoder<br>Singleturn 24 bit - with signal<br>connection RJ45 |
| Electrical connection    | Connector turnable                                                                     |
| Connector size           | 1                                                                                      |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 4,000 rpm |
| Optimum power           | 2.5 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 9,000 rpm |
| Max. permissible speed (inverter) | 8,000 rpm |
| Maximum torque                    | 49.0 Nm   |
| Maximum current                   | 70.00 A   |

| Recommended Motor Module |         |
|--------------------------|---------|
| Rated inverter current   | 18.00 A |
| Maximum inverter current | 54.00 A |
| Maximum torque           | 42.8 Nm |