

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7082-5WF74-1NH1




Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	3,000 rpm
Number of poles	10
Rated torque (100 K)	20.5 Nm
Rated current	16.00 A
Static torque (60 K)	17.5 Nm
Static torque (100 K)	21.0 Nm
Stall current (60 K)	13.40 A
Stall current (100 K)	16.00 A
Rotor moment of inertia	43.00 kgcm ²
Efficiency	94.0 %

Physical constants	
Torque constant	1.31 Nm/A
Voltage constant at 20° C	82.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.28 Ω
Rotary field inductance	4.2 mH
Electrical time constant	15.00 ms
Mechanical time constant	1.40 ms
Thermal time constant	2 min
Shaft torsional stiffness	76,000 Nm/rad
Net weight of the motor	23.7 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	80
Cooling	Water cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track
Electrical connection	Connector turnable
Connector size	1.5

Optimum operating point	
Optimum speed	3,000 rpm
Optimum power	6.4 kW

Limiting data	
Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	7,000 rpm
Maximum torque	55.0 Nm
Maximum current	54.00 A

Recommended Motor Module	
Rated inverter current	18.00 A
Maximum inverter current	54.00 A
Maximum torque	55.0 Nm

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	48.0 Nm
Braking torque	25.0 Nm
Power supply voltage	DC 24 V
Coil current	1.00 A
Permissible brake work	1,900 J
Opening time	220 ms
Closing time	65 ms