



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7084-5AC74-1NA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data        |                         |
|-------------------------|-------------------------|
| Rated speed             | 2,000 rpm               |
| Number of poles         | 10                      |
| Rated torque (100 K)    | 16.9 Nm                 |
| Rated current           | 8.40 A                  |
| Static torque (60 K)    | 16.8 Nm                 |
| Static torque (100 K)   | 20.0 Nm                 |
| Stall current (60 K)    | 7.60 A                  |
| Stall current (100 K)   | 9.00 A                  |
| Rotor moment of inertia | 45.10 kgcm <sup>2</sup> |
| Efficiency              | 93.0 %                  |

| Physical constants          |                                |
|-----------------------------|--------------------------------|
| Torque constant             | 2.21 Nm/A                      |
| Voltage constant at 20° C   | 141.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.53 Ω                         |
| Rotary field inductance     | 8.5 mH                         |
| Electrical time constant    | 16.00 ms                       |
| Mechanical time constant    | 1.50 ms                        |
| Thermal time constant       | 55 min                         |
| Shaft torsional stiffness   | 88,000 Nm/rad                  |
| Net weight of the motor     | 20.8 kg                        |

| Mechanical data          |                                                                                  |
|--------------------------|----------------------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                               |
| Motor type               | Compact                                                                          |
| Shaft height             | 80                                                                               |
| Cooling                  | Natural cooling                                                                  |
| Radial runout tolerance  | 0.050 mm                                                                         |
| Concentricity tolerance  | 0.100 mm                                                                         |
| Axial runout tolerance   | 0.100 mm                                                                         |
| Vibration severity grade | Grade A                                                                          |
| Degree of protection     | IP64                                                                             |
| Design acc. to Code I    | IM B5 (compatible with 1FT6)                                                     |
| Temperature monitoring   | Pt1000 temperature sensor                                                        |
| Color of the housing     | Standard (pearl dark gray similar to RAL 9023)                                   |
| Shaft end type           | Fitted key and keyway                                                            |
| Sensor design            | Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track |
| Electrical connection    | Connector turnable                                                               |
| Connector size           | 1                                                                                |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 2,000 rpm |
| Optimum power           | 3.5 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 8,000 rpm |
| Max. permissible speed (inverter) | 4,000 rpm |
| Maximum torque                    | 81.0 Nm   |
| Maximum current                   | 46.00 A   |

| Recommended Motor Module |         |
|--------------------------|---------|
| Rated inverter current   | 9.00 A  |
| Maximum inverter current | 27.00 A |
| Maximum torque           | 51.0 Nm |