

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7087-7SF70-1CB1



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	3,000 rpm
Number of poles	8
Rated torque (100 K)	33.0 Nm
Rated current	29.00 A
Static torque (60 K)	37.0 Nm
Static torque (100 K)	48.0 Nm
Stall current (60 K)	31.00 A
Stall current (100 K)	40.00 A
Rotor moment of inertia	41.60 kgcm <sup>2</sup>
Efficiency	93.0 %

### Physical constants

Torque constant	1.20 Nm/A
Voltage constant at 20° C	77.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.08 Ω
Rotary field inductance	2.1 mH
Electrical time constant	26.00 ms
Mechanical time constant	0.50 ms
Thermal time constant	25 min
Shaft torsional stiffness	45,500 Nm/rad
Net weight of the motor	45.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	80
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (new flange design)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Connector turnable
Connector size	1.5

### Optimum operating point

Optimum speed	3,000 rpm
Optimum power	10.4 kW

### Limiting data

Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	7,500 rpm
Maximum torque	150.0 Nm
Maximum current	170.00 A

### Recommended Motor Module

Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	96.0 Nm

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	48.0 Nm
Braking torque	25.0 Nm
Power supply voltage	DC 24 V
Coil current	1.00 A
Permissible brake work	1,900 J
Opening time	220 ms
Closing time	65 ms