

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7087-7SH71-1MA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data

Rated speed	4,500 rpm
Number of poles	8
Rated torque (100 K)	23.0 Nm
Rated current	24.00 A
Static torque (60 K)	37.0 Nm
Static torque (100 K)	48.0 Nm
Stall current (60 K)	35.00 A
Stall current (100 K)	45.00 A
Rotor moment of inertia	27.40 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.06 Nm/A
Voltage constant at 20° C	68.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.06 Ω
Rotary field inductance	1.7 mH
Electrical time constant	28.00 ms
Mechanical time constant	0.40 ms
Thermal time constant	25 min
Shaft torsional stiffness	60,000 Nm/rad
Net weight of the motor	43.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	80
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface
Electrical connection	Transverse facing to right site
Connector size	3

Optimum operating point

Optimum speed	4,500 rpm
Optimum power	10.8 kW

Limiting data

Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	8,000 rpm
Maximum torque	150.0 Nm
Maximum current	195.00 A

Recommended Motor Module

Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	85.0 Nm