

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7108-5AF71-1CH1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	3,000 rpm
Number of poles	10
Rated torque (100 K)	20.0 Nm
Rated current	12.00 A
Static torque (60 K)	58.0 Nm
Static torque (100 K)	70.0 Nm
Stall current (60 K)	28.00 A
Stall current (100 K)	36.00 A
Rotor moment of inertia	276.00 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.94 Nm/A
Voltage constant at 20° C	127.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.07 Ω
Rotary field inductance	1.7 mH
Electrical time constant	26.00 ms
Mechanical time constant	1.30 ms
Thermal time constant	95 min
Shaft torsional stiffness	96,000 Nm/rad
Net weight of the motor	65.1 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Connector turnable
Connector size	1.5

Optimum operating point

Optimum speed	2,000 rpm
Optimum power	8.2 kW

Limiting data

Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	4,500 rpm
Maximum torque	280.0 Nm
Maximum current	165.00 A

Recommended Motor Module

Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	150.0 Nm

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	85.0 Nm
Braking torque	35.0 Nm
Power supply voltage	DC 24 V
Coil current	1.60 A
Permissible brake work	5,300 J
Opening time	250 ms
Closing time	70 ms