

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7108-5SF71-1CG0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	3,000 rpm
Number of poles	10
Rated torque (100 K)	60.0 Nm
Rated current	38.00 A
Static torque (60 K)	74.0 Nm
Static torque (100 K)	91.0 Nm
Stall current (60 K)	46.00 A
Stall current (100 K)	57.00 A
Rotor moment of inertia	248.00 kgcm <sup>2</sup>
Efficiency	93.0 %

### Physical constants

Torque constant	1.60 Nm/A
Voltage constant at 20° C	101.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.04 Ω
Rotary field inductance	1.1 mH
Electrical time constant	26.00 ms
Mechanical time constant	1.30 ms
Thermal time constant	60 min
Shaft torsional stiffness	96,000 Nm/rad
Net weight of the motor	64.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Transverse facing to right site
Connector size	3

### Optimum operating point

Optimum speed	3,000 rpm
Optimum power	18.8 kW

### Limiting data

Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	5,600 rpm
Maximum torque	280.0 Nm
Maximum current	205.00 A

### Recommended Motor Module

Rated inverter current	60.00 A
Maximum inverter current	113.00 A
Maximum torque	177.0 Nm