



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7108-5WC71-1CG0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	2,000 rpm
Number of poles	10
Rated torque (100 K)	125.0 Nm
Rated current	47.46 A
Static torque (60 K)	100.0 Nm
Static torque (100 K)	125.0 Nm
Stall current (60 K)	37.20 A
Stall current (100 K)	45.30 A
Rotor moment of inertia	265.00 kgcm ²
Efficiency	95.0 %

Physical constants	
Torque constant	2.69 Nm/A
Voltage constant at 20° C	170.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.08 Ω
Rotary field inductance	1.9 mH
Electrical time constant	23.00 ms
Mechanical time constant	0.90 ms
Thermal time constant	2 min
Shaft torsional stiffness	126,000 Nm/rad
Net weight of the motor	68.6 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Water cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Transverse facing to right site
Connector size	3

Optimum operating point	
Optimum speed	2,000 rpm
Optimum power	26.2 kW

Limiting data	
Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	3,400 rpm
Maximum torque	330.0 Nm
Maximum current	141.50 A

Recommended Motor Module	
Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	214.0 Nm