

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7136-5SC71-5CG0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	2,000 rpm
Number of poles	8
Rated torque (100 K)	190.0 Nm
Rated current	81.00 A
Static torque (60 K)	195.0 Nm
Static torque (100 K)	235.0 Nm
Stall current (60 K)	79.00 A
Stall current (100 K)	98.00 A
Rotor moment of inertia	748.00 kgcm ²
Efficiency	95.0 %

Physical constants	
Torque constant	2.42 Nm/A
Voltage constant at 20° C	165.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.04 Ω
Rotary field inductance	1.5 mH
Electrical time constant	36.00 ms
Mechanical time constant	1.60 ms
Thermal time constant	25 min
Shaft torsional stiffness	301,000 Nm/rad
Net weight of the motor	114.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	132
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.125 mm
Axial runout tolerance	0.125 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Shaft end type	Plain shaft
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Terminal box transverse right

Optimum operating point	
Optimum speed	2,000 rpm
Optimum power	39.8 kW

Limiting data	
Max. permissible speed (mech.)	3,600 rpm
Max. permissible speed (inverter)	3,500 rpm
Maximum torque	510.0 Nm
Maximum current	245.00 A

Recommended Motor Module	
Rated inverter current	132.00 A
Maximum inverter current	210.00 A
Maximum torque	455.0 Nm