



Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LA5207-4AA60-Z
D22

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated voltage :	(6) 400 VD/690 VY, 50 Hz, 460 VD, 60 Hz					
Frequency :	50 Hz			60 Hz		
Rated power :	30.00 kW			34.50 kW		
Rated speed :	1465 1/ min			1765 1/ min		
Rated torque :	195.6 Nm			186.7 Nm		
Rated current (IE) :	VD	VY		VD		
	56.00 A	32.46 A		55.00 A		
Starting / rated current :	7.0			7.0		
Breakdown / rated torque :	3.2			3.2		
Starting / rated torque :	2.6			2.6		
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	90.7%	90.7%	89.7%	91.0%	91.0%	90.0%
Power factor :	0.86	0.83	0.75	0.86	0.83	0.75
Efficiency class :	IE1			-/-		

Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	65 dB(A)	69 dB(A)
Moment of inertia :	0.24 kg*m²	
Bearing DE :	6212 ZC3	
Bearing NDE :	6212 ZC3	
Type of bearing :	Locating bearing NDE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	200 L
Design of electrical machine :	(0) IM B3 / B6 / B7 / B8 / V5 without canopy
Weight in kg, without optional accessories :	157.00 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	
Type of terminal box :	gk 430
Contact screw thread :	
Max. cross-sectional area :	
Cable diameter from ... to ... :	
Cable entry :	
Cable gland :	

Special design:

D22 motor without CE character for export outside the EEA (see EU regulation 640/2009)