

Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LA7070-4AB62

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated voltage :		(6) 400 VD/690 VY, 50 Hz, 460 VD, 60 Hz					
Frequency :		50 Hz			60 Hz		
Rated power :		0.25 kW			0.29 kW		
Rated speed :		1350 1/ min			1650 1/ min		
Rated torque :		1.8 Nm			1.7 Nm		
Rated current (IE) :		VD	VY		VD		
		0.77 A	0.45 A		0.76 A		
Starting / rated current :		3.0			3.3		
Breakdown / rated torque :		1.9			2.0		
Starting / rated torque :		1.9			1.9		
		4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %		61.9%	60.4%	55.9%	61.9%	60.4%	55.9%
Power factor :		0.78	0.72	0.61	0.77	0.71	0.59
Efficiency class :		-/-			-/-		

Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	44 dB(A)	48 dB(A)
Moment of inertia :	0.00052 kg*m ²	
Bearing DE :	6202 2ZC3	
Bearing NDE :	6202 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	071 M
Design of electrical machine :	(2) IM B14 / V18 / V19, standard flange
Weight in kg, without optional accessories :	4.80 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	
Type of terminal box :	gk 030
Contact screw thread :	
Max. cross-sectional area :	
Cable diameter from ... to ... :	
Cable entry :	
Cable gland :	

Special design: