



Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LA7096-4AA91-Z
C01+D22+G26+K82+L1L

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated voltage :		380 VD/660 VY, 50 Hz					
Frequency :		50 Hz			60 Hz		
Rated power :		1.50 kW			1.75 kW		
Rated speed :		1420 1/ min			1720 1/ min		
Rated torque :		10.1 Nm			9.7 Nm		
Rated current (IE) :		VD	VY		VD		
		3.63 A	2.09 A		3.45 A		
Starting / rated current :		5.3			5.6		
Breakdown / rated torque :		2.6			2.6		
Starting / rated torque :		2.4			2.4		
		4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %		77.2%	77.7%	74.2%	81.5%	81.5%	80.5%
Power factor :		0.81	0.76	0.66	0.82	0.77	0.67
Efficiency class :		IE1			IE1		

Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	48 dB(A)	52 dB(A)
Moment of inertia :	0.0033 kg*m²	
Bearing DE :	6205 2ZC3	
Bearing NDE :	6004 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	090 L
Design of electrical machine :	(1) IM B5 / V1 without canopy
Weight in kg, without optional accessories :	15.60 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	
Type of terminal box :	gk 127
Contact screw thread :	
Max. cross-sectional area :	
Cable diameter from ... to ... :	
Cable entry :	
Cable gland :	

Special design:

C01	Brake supply voltage AC 400V, 50Hz
D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)
G26	Mounting a brake
K82	Mechanical manual brake release with lever
L1L	380 VD/660 VY at 50 Hz